

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Houghton (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S 4 T 51N R 35W	3
	S 4 T 51N R 35W	10
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on 10 03/12/13
3 06/10/13 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(3 - Sec. 4) North 1/16 corner between Sections 4 and 5. Not previously monumented. The original
plat of this township gives distances 20.13 ch. North to Section corner and 20.00 ch. South to
Quarter corner.

(10-Sec. 4) South 1/16 corner between Sections 4 and 5. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(3-Sec. 4) Established the position for the corner on the Section line between Section corner
1232.30' north and Quarter corner 1224.34' south, proportionate to the original record.

(10-Sec. 4) Established the position for the corner midway and on the Section line between Section
corner 1355.12' south and Quarter corner 1355.12' north.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(3) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
6" Sugar N05°W 21.6' mrkd "1/16S BT"
5" Sugar N87°E 10.3' do
7" Sugar S28°W 14.2' do
5" Y.Birch S78°W 16.5' do
Set sq'd cedar post adjacent.
E= 7865544.500 N= 231022.756

(10) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
7" Hemlock S59°E 33.9' mrkd "1/16S BT"
4" Hemlock S10°W 16.6' do
9" Maple S58°W 53.7' do
5" Balsam N80°W 46.7' do
Set sq'd cedar post adjacent.
E= 7865532.510 N= 230236.719

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum)
Coord. Ref.=NGS PID RL0593: N= 221669.506 m. E= 7868965.488 m.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 08/20/2013

For the Michigan Department of Natural Resources, Forest Resources Division

