

Houghton Co.

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____	T. 52 N. 35 W. XX	J12
2. PROPERTY CONTROLLING IN SECTION 35, T. 52 N. 35 W. XX		5
3. MISCELLANEOUS PROPERTY IN SECTION_____, T._____, N._____, R._____, E._____, W._____,		
4. LOT NO._____, RECORDED PLAT_____		
5. PRIVATE CLAIMS_____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on June 26, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19_____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner 5: Not Set on Original Survey Nor Subsequently Apparently.

Corner J12: Corner was previously set by Billy D. Buckler from erroneous $\frac{1}{4}$ corner between 26/35. After locating original $\frac{1}{4}$ corner, Section 35 was re-subdivided.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner 5: Established on subdivision of Section.

Corner J12: Re-established on subdivision of section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner 5: Set 1" I.D.x36" Iron Pipe with 4" aluminum cap.
7" Maple S29W 5.4 ft. 1/16S, BT
6" Yellow Birch S89E 9.4 ft. 1/16S, BT
5" Maple N04W 27.8 ft. 1/16S, BT
12" Yellow Birch squared up N04W 3.7 ft.

Corner J12: Set 1" I.D.x40" Iron Pipe with 4" aluminum cap.
8" Maple S46E 5.6 ft. $\frac{1}{4}$ S, BT
7" Sugar N32E 8.0 ft. $\frac{1}{4}$ S, BT
9" Yellow Birch S69W 8.5 ft. $\frac{1}{4}$ S, BT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE July 14, 1978
CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR
Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

