

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

HOUGHTON COUNTY

FOR CORNERS OF—	LOCATED IN—	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 52N N. R. 35 X. W.	B-11 C-12
2. PROPERTY CONTROLLING IN SECTION 35	T. 52N N. R. 35 X. W.	3
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. R. E. W.	
4. LOT NO. —, RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on see below, 19__, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on __, 19__, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and or subsequent restoration:

Corner 3: Not set on original survey nor subsequently apparently.

Corner B-11: Original monument and accessories not found.

Corner C-12: Original monument and accessories not found.

B. Description of corner evidence found and or method applied in restoring or re-establishing corner.

Corner 3: Established 5-5-82 midway and on line between corners north and south.

Corner B-11: Restored on line at record distance between corners east and west.

Corner C-12: Restored 7-14-82 midway and on line between section corners north and south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner 3: Set 1" I.D. by 32" Iron Pipe w/4" alum. cap.

9" Sugar S51W 16.1 ft. 1/16S, BT

6" Sugar N33W 12.0 ft. 1/16S, BT

8" Sugar N51E 12.8 ft. 1/16S, BT

Corner B-11: Set 1" I.D. by 32" Iron Pipe w/4" alum. cap.

17" Sugar N64E 2.0 ft. 1/4S, NBT

14" Sugar S17W 16.5 ft. 1/4S, NBT

6" Sugar N63W 11.2 ft. 1/4S, NBT

Corner C-12: Set 1" I.D. by 32" Iron Pipe w/4" alum. cap.

6" Sugar N05W 9.2 ft. 1/4S, NBT

16" Sugar N72E 14.8 ft. 1/4S, NBT

8" Sugar S31W, 8.1 ft. 1/4S, NBT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY _____

CHIEF OF SURVEY PARTY

MICHIGAN REGISTERED LAND SURVEYOR

Keith L. Sackett

Department of Natural Resources

DATE 2-16-83

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET