

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Houghton (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 17 T 52N R 36W	9
	S T R	(GCDB 260440)
	S 17 T 52N R 36W	5
	S T R	(GCDB 240460)
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 10/31/13 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
Instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(9-Sec. 17) East 1/16 corner, Section 17. Not previously monumented.

(5-Sec. 17) North 1/16 corner, Section 17. Not previously monumented.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(9-Sec. 17) Established the position for the corner midway and on a straight line between Quarter  
corner 1326.84' east and the Center of Section 17 1326.84' west.

(5-Sec. 17) Established the position for the corner midway and on a straight line between Quarter  
corner 1529.06' north and the Center of Section 17 1529.06' south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(9) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
10" Sugar N14°W 16.7' mrkd "1/16S BT"  
7" Sugar N30°E 14.2' do  
9" Sugar S51°E 10.4' do  
12" Sugar S77°W 7.75' do  
Set sq'd cedar post adjacent.  
E= 7855561.288 N= 237148.370

(5) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
6" Sugar N08°W 6.85' mrkd "1/16S BT"  
5" Y.Birch N62°E 14.0' do  
6" Hemlock S05°W 11.2' do  
6" Y.Birch S59°W 25.5' do  
Set sq'd cedar post adjacent.  
E= 7855155.863 N= 237628.967

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum).  
Coord. Ref.=NGS PID RL0502: N= 234995.272 m. E= 7857774.766 m.

Signed by Stephan J. Szyszkoski Date 11/18/2013  
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division