

# LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Houghton

(County)

Located In:

Corner Code #

## 1. Public Land Survey

T 53NR 34N E4  
T 53NR 34N C3  
T R  
T R  
T R  
T R  
T R  
T R

## 2. Property Controlling in Section

S T R  
S T R  
S T R  
S T R

## 3. Miscellaneous Property in Sec.

S T R  
S T R  
S T R

Register of Deeds Stamp & File Number

## 4. Lot No. , Recorded Plat

## 5. Private Claims

C3 Jul 08 2003

E4 Jul 10 2003

I, Stephan J. Szyszkoski, in a field survey on                     , 20           do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

## A. Description of original monument and accessories and/or subsequent restoration:

(E4) Quarter corner common to Sections 8 and 9. 1846: Established by Sylvester Higgins: North between Sec. 8&9...40.00 Set 1/4 sec. cor. post. Y.Birch 24 N50W 24, Y.Birch 18 S35E 27. ... 80.00 Set post cor. sec. 4,5,8,9. 1919: Notes of P.A.Larson state "Iron pipe set S50E 16' from original B.T. Birch 24" S35E 23' to broken BT. Marked Sugar 17" East 5". Larson shows distances 2559.2' South and 2679.1' North to adjacent Section corner monuments. Larson's sketch of the subdivision of the W1/2 of Sec. 9 shows the angle between section corners here is 181 deg. 09' (clockwise from E5).

(C3) Corner common to Sections 5-6-7-8. 1846: Established by Sylvester Higgins: North between Sec. 7 and 8...80.00 Set post cor. Sec. 5,6,7,8. Sugar 20 N30W 20, Sugar 15 S50E 25. 1846 distances: to A3 79.18 chains, to C4 40.00 chains, to D3 39.95 chains, to C1 79.80 chains. 1992: Notes of P.A.Larson state "at cor set Hem post B.T. sug org'l S30E 13.3'. Cent W.F.Hem tree. Marked Sug 16" S50E 20.5". And also on a P.A.Larson sketch: "N.Hem 26" N.E. 26.3". I presumed that "N." means "New". No distances to adjacent corners are noted by Larson.

## B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(E4) The original post and accessories were not recovered. Found a 1.5" ID iron pipe, which appears to have been in place for many years, at the intersection of very old cutting lines East and South. Distance north to Section corner is 2674.99', agreeing reasonably with Larson's measure. The distance south to E5 was found to be 2557.45', 82.55' shorter than the GLO record but agreeing well with Larson. I measured the angle noted above and found it to be 181 deg. 09'48". I judged the pipe to be Larson's monument and the best available evidence of the position of the original corner.

(C3) The original post and accessories were not recovered. Larson's post and NBTs were not recovered. Found no acceptable evidence of the position of the original corner on the ground. Reestablished the corner by proportionate measurement to the original record between A3 5318.41' West, C4 2655.04' South, D3 2684.67' East, and a found 1.5" ID iron pipe 5297.35' North. I do not know if the pipe to the North marks the standard corner or the closing corner.

## C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(E4) Found 1.5" ID iron pipe. Blazed, scribed, and set measuring nails in:  
6" Sugar N35E 11.9' "1/4S NBT"  
4" Sugar S52E 18.2' do  
6" Sugar S40W 44.4' do  
9" Sugar N79W 11.0' do  
Set sq'd Maple post adjacent. Bearings are magnetic. Distances are to nail with tag.

(C3) Set 1"IDx32" I.pipe with 4" alum. MDNR cap. Blazed, scribed, and set measuring nails in:  
9" Sugar N56E 7.8' "S5 NBT"  
10" Sugar S49E 36.5' "S8 NBT"  
10" Sugar S27W 5.7' "S7 NBT"  
5" Sugar N35W 14.3' "S6 NBT"  
Set sq'd Sugar post adjacent. Bearings are magnetic. Distances are to nail with tag.



Signed by Stephan J. Szyszkoski

Date 8/11/03

Surveyor's Michigan License No. 33986