JAN 192001

2000 REMONUMENTATION Reman Liber 3, Page 83

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970	
For corners in	STATE OF MICHIGAN
Huron Located in: Comer Code #	HURON COUNTY RECORDED
1. Public Land Survey Sherman T15N R 16E	20 SEP 2000 2:07 PM FRANCES L. HOLDWICK
2. Property Controlling S T R	REGISTER OF DEEDS
4. Lot No, Recorded Plat	
5. Private Claims	2 6 4 5 4 4 7 2 4 1
requirements of P.A. 74. Michigan P.A. of 1970, the corner points mentioned in liconformance with regulations and rules therefore as required in the current manual. United States Department of the Interior, Bureau of Land Management or by a decretat the corner points mentioned in lines 3, 4 and 5 above were in conformance with Board of Land Surveyors or by a Decree of a Court of Law; established, re-recovered, found as expressed below:	nes 1 and 2 above were in of survey instructions of the se of a Court of Law and /or thin the rules of the Michigan established, monumented, 8 19 20 21 22 23 24
NOTE: Not more than 2 corners, all in the same town and range, may be ron this certificate.	30 29 28 27 26 25
· · · · · · · · · · · · · · · · · · ·	11 12 -31 -32 -33 -34 -35 -36
Set quarter section post Birch 8", S64°W, 6 Links Hemlock 11", N37°W, 25½ Links L.C.R.C NONE County Surveyor Records - NONE Recorded St Unrecorded	Surveys - Little, 5-20-95, Liber 5, Page 159, F.I.R. Surveys - Chope, 3-27-71, Certificate shows Corner Milletics, 6-4-93, 5/8" Bar Milletics, 5-22-96, 5/8" Bar Case, 9-18-96, Certificate shows Corner Milletics, 4-29-97, 5/8" Iron Bar
B. Description of corner evidence found and/or method applied in resto	ring or reestablishing corner:
A-10 W 1/4 Cor, Section 30, T15N-R16E Found 5/8" Iron Bar Accepted as the best available evidence of the original corner position (Intersection of White Rock Road & Edwards R	load)
C. Description of monument for corner and accessories established to p A-10 W 1/4 Cor, Section 30, T15N-R16E Found 5/8" Iron Bar N45°W 48.80' to Nail in Power Pole S45°W 50.20' to Nail in Telephone Pole S45°E 57.00' to Face of Large Rock S50°E 50.90' to Nail in Fence Post	erpetuate locating the position of the corner: Charles S. Getz Land Surveyor No. 25843
N60°E 35.15' to Stop Sign North 2642.04' to NW Cor, Sec 30, T15N-R16E South 2629.00' to SW Cor, Sec 30, T15N-R16E	Malonal Sundi
Signed by Charles S. Getz	Date June 3, 2000
Surveyor's Michigan License No. 25843	
PEER GROUP APPROVED AT MEETING RUB HELD September 18, 2000 RUB	FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 17 REVISED MAY 14,18