

JAN 19 2001

SECTION

2000 REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

Re-Monumented, Page 88

STATE OF MICHIGAN  
HURON COUNTY  
RECORDED

For Corners in

Huron  
(County)

Located in:

Corner Code #

29 NOV 2000 11:20 AM

FRANCES L. HOLDWICK  
REGISTER OF DEEDS

1. Public Land survey: Sebewaing T 15 N R 9 E  
T \_\_\_\_\_ R \_\_\_\_\_  
T \_\_\_\_\_ R \_\_\_\_\_  
T \_\_\_\_\_ R \_\_\_\_\_
2. Property Controlling S 7 T \_\_\_\_\_ R \_\_\_\_\_ 0001  
in Section S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_
3. Miscellaneous S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_  
Property in Sec. S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_
4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_
5. Private Claims \_\_\_\_\_

Register of Deeds Stamp & File Number

I, James T. Meek, in a field survey on October 1, 2000,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules thereof as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:  
Original survey, West Bdy. T15NR9E, 1821, Joseph Wampler D.S.

A-0001 Witness to Meander Corner of Section 7, T15NR9E

Post

No bearing trees taken

County Surveyor's Record: none

Recorded Surveys: none

LCRC: N. Akron Township, Page 35

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-0001 Witness to Meander Corner of Section 7, T15NR9E

Found Brass Cap in concrete

Accepted as best available evidence of the original corner position

Per Tuscola County LCRC, N. Akron Township, Page 35

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-0001 Witness to Meander Corner of Section 7, T15NR9E

Brass cap in concrete

From which:

1/4" iron w/cap bears S45E°E, 297.62'

1/4" iron w/cap bears South, 15.0'

1/4" pipe bears S80°W, 19.4'


Tag in 6" Ash bears N35°W, 5.7'

M-3, T15NR8E Corner of Sections 1 & 12, bears S0°01'23"E, 1040.00'

Signed by \_\_\_\_\_ Date \_\_\_\_\_

Surveyor's Michigan License No. 39089

APPROVED AT PEER BOARD MEETING 11-02-00 RdB



FORM NO. 100-1, REVISED JAN. 28, 1977  
REVISED MAY 14, 1977  
REVISED JAN., 1981  
REVISED OCT., 1995