

HILLSDALE COUNTY REMONUMATION PROGRAM LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

LIBER 3 PAGE 311

021815

For corners in HILLSDALE COUNTY SCIPIO TWP.	Located In:	Corner Code #	RECORDED HILLSDALE CO. MICH. 99 AUG. 23 PM 4: 00
1. Public Land Survey	T <u>5S</u> R <u>3W</u> TR TR 	<u>G-6</u>	REG. OF DEFOS
2. Property Controlling in Section	S T R S T R		Register of Deeds Stamp & File Number
3. Miscellaneous Property in Sec.	S R T R T R		
	corded Plat		ABCDEFGHJKI
under requirements of P.A. 74 and 2 above were in conformal manual of survey instructions Management or by a decree o 3, 4 and 5 above were in conformal process.	4, Michigan P.A. of 1970, the conce with regulations and rules to find the United States Department of Law and for that the formance with the rules of the Mormance with the Rules of the	, 19 99 do hereby state that corner points mentioned in lines 1 herefore as required in the current and of the Interior, Bureau of Land e corner points mentioned in lines Michigan Board of Land Surveyors I, monumented, recovered, found	2 6 5 4 3 2 1 1 3 4 7 8 9 10 11 12 13 15 14 13 7 8 19 20 21 22 23 24
NOTE: Not more than 2 comon this certificate.	ners, all in the same town and ra	nge, may be recorded	9 29 28 27 26 25
QUARTER CORNER COMMON TO SECTIONS 15 &16			11 12 31 32 33 34 35 36
A. Description of original n	nonument and accessories and	lior subsequent restoration:	

1825: GLO CORNER SET

1872: GEO. A. MARK, SURVEYOR, SURVEY #660, STONE & BRICK

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND PK NAIL

NO EVIDENCE OF STONE OR BRICK

SET 3/4" IRON (IN PLACE OF PK NAIL) WITH REMON CAP IN CAST IRON MONUMENT BOX

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

3/4" IRON WITH REMON CAP IN CAST IRON BOX

4.3' W OF C/L OF N-S ROAD

N 67 W 26.85' - NAIL AND CAP S. SIDE 44" OAK

N 84 W 28.84" - FACE OF CONCRETE POST

N 32 E 60.62' - TOP/CENTER OF TELEPHONE PEDESTAL

S 22 W 94.22" - NAIL AND CAP W. SIDE 36" ASH

S 80 E 58.15' - N-W CORNER OF BUILDING (NOT PORCH)

IN LINE WITH FENCE LINE RUNNING EAST AND WEST

AND IS ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION

OF THE POSITION OF THE ORIGINAL CORNER.

Signed by

Date <u>JUNE 18, 1999</u>

OF MICHIE

EDWARD

W. REED

LAND

SURVEYOR

NO. 33985

ED LAND SU

EDWARD W. REED

Surveyor's Michigan License No.___