

007941

RECORDED
HILLSDALE CO. MICH.

98 AUG 7 AM 10 10

Judy VanZandt
REC. OF DEEDS

LIBER 3 PAGE 254

HILLSDALE COUNTY REMONUMATION CORNER LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

HILLSDALE COUNTY
ADAMS TWP.

Located In:

Corner Code

1. Public Land Survey

T 6 S R 2 W

I-7

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S

T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

SURVEY &
REMONUMENTATION

FEB 23 1999

4. Lot No. , Recorded Plat

5. Private Claims

SECTION

I, EDWARD W. REED, in a field survey on JULY 26, 19 98

do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

CORNER COMMON TO SECTIONS 14-15-22-23

A. Description of original monument and accessories and/or subsequent restoration:

1983: T. CLOW, PARTY CHIEF OF RINGENBERG ENG. FIELD NOTES INDICATE 1/2" IRON STAKE

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" IRON STAKE AS WITNESSED IN FIELD NOTES, FOUND NO OTHER EVIDENCE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

REMOVED 1/2" IRON, SET 3/4" X 30" REBAR IRON WITH REMON CAP IN CI-MONUMENT BOX 4" BELOW GRAVEL ROAD SURFACE

PK NAIL WEST SIDE POWER POLE,	S 25 W	71.03'
PK NAIL E SIDE 6" WALNUT,	N 45 W	49.12'
PK NAIL SE SIDE 24" MAPLE	N 80 E	93.42'
PK NAIL N SIDE POWER POLE	S 30 E	84.25'

AND IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER

Signed by

EDWARD W. REED

Date

AUGUST 5, 1998

Surveyor's Michigan License No. 33985

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

