

ACCEPTED BY THE HILLSDALE COUNTY  
SURVEY PEER GROUP AS THE OFFICIAL  
CORNER UNDER MICHIGAN PUBLIC ACT 345  
JAN 1990 AT A MEETING HELD ON  
JAN 1990 AT HILLSDALE CO. MI.

LIBER 5 PAGE 33

034951

RECORDED  
HILLSDALE CO. MICH.

00 OCT 11 AM 10:41

HILLSDALE COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

HILLSDALE

(County)

ADAMS TWP.

Located In:

Corner Code #

1. Public Land Survey

T6S R2W

B-11

2. Property Controlling  
in Section

S

T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

S

T R

4. Lot No.

Recorded Plat

5. Private Claims

SURVEY &  
REMONUMENTATION

JAN 12 2001

SECTION

Register of Deeds Stamp & File Number

|    |    |    |    |    |    |    |   |   |   |   |   |   |   |
|----|----|----|----|----|----|----|---|---|---|---|---|---|---|
| 1  | A  | B  | C  | D  | E  | F  | G | H | I | J | K | L | M |
| 2  | 6  | 5  | 4  | 3  | 2  | 1  |   |   |   |   |   |   |   |
| 3  |    |    |    |    |    |    |   |   |   |   |   |   |   |
| 4  | 7  | 8  | 9  | 10 | 11 | 12 |   |   |   |   |   |   |   |
| 5  |    |    |    |    |    |    |   |   |   |   |   |   |   |
| 6  | 18 | 17 | 16 | 15 | 14 | 13 |   |   |   |   |   |   |   |
| 7  |    |    |    |    |    |    |   |   |   |   |   |   |   |
| 8  | 19 | 20 | 21 | 22 | 23 | 24 |   |   |   |   |   |   |   |
| 9  |    |    |    |    |    |    |   |   |   |   |   |   |   |
| 10 | 30 | 29 | 28 | 27 | 26 | 25 |   |   |   |   |   |   |   |
| 11 |    |    |    |    |    |    |   |   |   |   |   |   |   |
| 12 | 31 | 32 | 33 | 34 | 35 | 36 |   |   |   |   |   |   |   |
| 13 |    |    |    |    |    |    |   |   |   |   |   |   |   |

I, Frederick J. Cutcher, in a field survey on Sept 15, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO, Robert Clark, Jr., Apr. 1825: Set Quarter Section Post; B. Oak 5" N. 7-1/2° E. 24-1/2 lks.; B. Oak 20" S. 82° W. 34-1/2 lks.

Geo. Mark, Survey #927, May 16, 1882: Stone, earthen & brick.

Robert E. Burris, Sr., Oct. 10, 1974, LCRC L. 1 - P. 427, #4623: Set R.R. Spike (See LCRC).

Alan E. Ringenberg: Surveys Oct. 8, 1982, Oct. 11, 1982, Mar. 16, 1984: R.R. spike 5' S. of centerline Bacon Rd.; (references are shown on recorded survey).

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found R.R. spike 5.6' S. of centerline road. All of the references in above LCRC remain.

Dug at position of R.R. spike. Nothing else found.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Replaced R.R. spike with 3/4" x 30" iron with remonumentation cap in monument box and is accepted as the best available evidence of the position of the original corner.

5.6' S. of centerline Bacon Road.

Fd. P.K. in Util. Pole N. 13° E. 32.04'

Set Nail & Spotter in 30" Hickory S. 47° W. 33.79'

N.E. corner house foundation S. 10° W. 119.03'

Set Nail & Spotter in 24" Walnut South 79.41'

Set Nail & Spotter in 18" Hickory N. 30° E. 62.41'

Signed by Frederick J. Cutcher

Surveyor's Michigan License No.

24592

Date

