



LIBER 3 PAGE 196

127737

RECORDED
HILLSDALE CO. MICH.

HILLSDALE COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

'97 OCT 30 AM 10 18

Julia VanZandt
REC. OF DEEDS

For corners in

Hillsdale
(County)

Located In:

Corner Code #

1. Public Land Survey

T 6S R 3W

D-13

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

SURVEY &
REMONUMENTATION

FEB 11 1998

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

Frederick J.

Cutcher

, in a field survey on 9/25, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original Government Survey by William Brookfield, 1825: Ash 14" N. 11° E. 21½ links;
Ash 5" N. 55° W. 13 links.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

On 9-25-97 I found nothing.

No witnesses were found. Set corner 1/2 way and on line with corner C-13 and E-13.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I set a County remonumentation bar and cap in a monument box 1/2 way and on line with C-13 and E-13 and is accepted as best available evidence of the position of the original corner.

2' North of centerline Bankers Road. 51.48' West of D-1, T7S, R3W.

Nail & spotter East side util. pole N. 38° E. 29.39'

Nail & spotter N.W. side util. pole S. 67° W. 62.89'

S.W. corner deck on house N. 30° E. 123.76'

Top cen. tel stan. N. 78° W. 130.50'

Signed by

Frederick J. Cutcher

Date 10/29/97

Surveyor's Michigan License No. Frederick J. Cutcher 24592

