



LIBER 3 PAGE 290

REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

12392

RECORDED
HILLSDALE CO. MICH.

'98 DEC 4 AM 11 47

For corners in

HILLSDALE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 7S R 1W A-6

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

Judy VanZandt
REG. OF DEEDS

SURVEY &
REMONUMENTATION

FEB 23 1999

SECTION

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Jeffrey A. Bieszk, in a field survey on 25 Nov, 19 98 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		19		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

County Surveyor (Geo. A. Marks 1882)
Iron Bar

LCRC (Bruce Leone L 573, P 435)
Harrison Monument.
SW Corner of Brick Building N 49 E 51.08 ft.
PK Power Pole N 26 E 58.45 ft..
SE Corner Block Building N 44 W 49.42 ft.
NE Corner Block Building S 71 W 86.40 ft.
PK Power Pole S 47 W 37.10 ft.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found Harrison monument set by Bruce Leone, who found 1" iron bar 37" below surface and 1" iron 21" long over iron bar 16" below surface an railroad spike at surface, dug and found one of the irons as found by Leone. Accepted as the best available evidence to the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 36" iron w/cap in Monument Box
SW Corner of Brick Building N 49 E 51.00 ft.
Nail & Tag Power Pole S 50 W 37.40 ft.
SE Corner Block Building N 44 W 48.52 ft.
NE Corner Block Building N 50 E 69.70 ft.



Signed by
Surveyor's Michigan License No. 41093

Date 4 December 1998