



036200

RECORDED  
HILLSDALE CO. MICH.

NOV 17 PM 3:41

LIBER 5 PAGE 53

HILLSDALE COUNTY REMONUMENTATION CORNER  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

Judy VanZandt  
REG. OF DEEDS

For corners in

HILLSDALE COUNTY  
READING TWP (County)  
1. Public Land Survey T 7 S R 4 W I-5  
T R  
T R  
T R  
2. Property Controlling S T R  
S T R  
3. Miscellaneous S T R  
Property in Sec. S T R

SURVEY &  
REMONUMENTATION

JAN 12 2001

SECTION

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, EDWARD W. REED, in a field survey on NOVEMBER 16, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

CORNER COMMON TO SECTIONS 10, 11, 14, AND 15, READING TOWNSHIP,  
HILLSDALE COUNTY, MICHIGAN

A. Description of original monument and accessories and/or subsequent restoration:

1825: WM. BROOKFIELD-CORNER SET  
1882: GEO MARK-STONE  
1997: A. RINGENBERG-SET PK NAIL IN CENTERLINE OF M-49 BETWEEN SE CORNER SECTION 11 AND SOUTH CORNER OF SECTION 10

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

CORNER NOW GONE DUE TO CONSTRUCTION OF HIGHWAY M-49  
ACCEPTED A. RINGENBERG'S NAIL AS MOST COMMON USED CORNER AS SEVERAL SURVEYORS  
HAVE USED THIS CORNER  
SET 3/4" X 30" REBAR IRON WITH REMON CAP IN CAST IRON BOX FLUSH WITH PAVED ROAD SURFACES

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:


SET 3/4" X 30" REBAR IRON WITH REMON CAP IN CAST IRON BOX FLUSH WITH PAVED ROAD SURFACE  
28" MAPLE S37E 119.13'  
ARTESIAN WELL PIPE S75E 113.30'  
FENCE CORNER POST S17E 102.15'  
NAIL IN POWER POLE N38W 58.18'  
WEST END OF ROAD CULVERT N50E 41.9'

AND IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE  
OF THE POSITION OF THE ORIGINAL CORNER

Signed by Edward W. Reed  
EDWARD R. REED

Surveyor's Michigan License No. 33985

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													



Date NOVEMBER 16, 2000