

034008

RECORDED
HILLSDALE CO. MICH.

00 SEP 14 AM 11:35

HILLSDALE COUNTY REMONUMENTATION PROGRAM
LAND CORNER RECORDATION CERTIFICATE
 Filing Requirement of Act 74, Mich. P.A. 1970



For corners in

**SURVEY &
REMONUMENTATION**

JAN 12 2001

SECTION

Register of Deeds Stamp & File Number

HILLSDALE COUNTY Located In: _____ Corner Code # _____
READING TWP

1. Public Land Survey T 7 S R 4 W K-5
 T _____ R _____
 T _____ R _____
 T _____ R _____
2. Property Controlling in Section S _____ T _____ R _____
 S _____
 T _____ R _____
3. Miscellaneous S _____
 T _____ R _____
- Property in Sec. S _____
 T _____ R _____
4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, EDWARD W. REED, in a field survey on AUGUST 17, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

CORNER COMMON TO SECTIONS 11, 12, 13, AND 14

A. Description of original monument and accessories and/or subsequent restoration:

1825: WM BROOKFIELD, CORNER SET
 1877: GEO MARKS - TILE
 1997: A. RINGENBERG - RAILROAD SPIKE AND WITNESSES

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND RAILROAD SPIKE PAINTED GREEN FITTING WITNESSES OF RINGENBERG
 DUG BELOW, FOUND NOTHING ELSE, ACCEPTED AS CORNER
 SET 3/4" x 30" REBAR IRON, REMON CAP IN CAST IRON MONUMENT BOX FLUSH WITH PAVED ROAD SURFACE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

IN LINE WITH FENCE RUNNING NORTH		
CENTER OF 16" WALNUT	N60°W	76.5'
FACE OF STEEL ANCHOR POST	NORTH	33.4'
CENTER OF EAST - WEST ROAD	NORTH	6.0'
CENTER OF 30" CHERRY	S66°W	35.4'
CENTER OF 8" TRIPLE MAPLE	S31°E	27.1'

AND IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE
 OF THE POSITION OF THE ORIGINAL CORNER.

Signed by

EDWARD W. REED

DATED: AUGUST 17, 2000

Surveyor's Michigan License No. 33985

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

