



LIBER 5 PAGE 21
REMONUMENTATION

034939

RECORDED
HILLSDALE CO. MICH.

00 OCT 11 AM 10:31

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

HILLSDALE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 8S R 1W D-11

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

SURVEY &
REMONUMENTATION

JAN 12 2001

SECTION

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Jeffrey A. Bieszk, in a field survey on 6 Oct. 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

GLO set by Ziba Swan (1824)
28" Beech S68W 30 lks
18" Hickory S80E 49 lks

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found R.R. Spike centerline of Road and on occupation line North and South. Dug and found nothing else.
Accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 36" iron w/cap in Monument Box
Nail w/tag 16" Elm North 93.53 ft.
Nail w/tag 6" Cherry S 05 E 22.43 ft.
Nail w/tag 30" Maple S 10 W 31.00 ft.
Nail w/tag 20" Maple Stump S 40 W 36.71 ft.



Signed by _____

Surveyor's Michigan License No. 41093

Date OCTOBER 11, 2000