



034944

RECORDED
HILLSDALE CO. MICH.

00 OCT 11 AM 10:31

LIBER 5 PAGE 26

REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

HILLSDALE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 8S R 1W I-11

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

SURVEY &
REMONUMENTATION

JAN 12 2001

SECTION

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Jeffrey A. Bieszk, in a field survey on 6 Oct. 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO set by Ziba Swan (1824)

14" B. Oak S57W 5 lks

3" Ironwood N80E 7 lks

Larry M. Gerschbacher LCRC L552 P27 & 28

Found 1/2" iron bar

Sign Post N56E 47.60 ft.

Phone Riser S56E 45.00 ft.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" iron as witnessed by Gerschbacher. The iron was 2.5 feet South and 8 feet West of intersection of roads. He measured West Line of Section 35 which showed SW corner to West Quarter corner being 2630.46 feet and West Quarter Corner to NW corner as 2630.26 feet and only being 4 second different in bearing. Dug and found nothing else. Accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 36" iron w/cap in Monument Box

Nail w/tag Power Pole N 20 E 152.16 ft.

Stop Sign N 03 W 59.28 ft.

Phone riser S 60 E 58.31 ft.

Stop Sign S 25 E 45.64 ft.



Signed by [Signature]
Surveyor's Michigan License No. 41093

Date OCTOBER 11, 2000