

ACCEPTED BY THE  
SURVEY PEER GROUP AS THE  
CORNER UNDER MICHIGAN PUBLIC ACT  
OF 1974-05 MEETING FIELD  
AL RINGENBERG, CO. REG.

LIBER 5 PAGE 28  
REMONUMENTATION

034946

RECORDED  
HILLSDALE CO. MICH.

00 OCT 11 AM 10:31

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

*Jeffrey A. Bieszk*  
REG. OF DEEDS

For corners in

HILLSDALE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 8S R 1W K-11

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

SURVEY &  
REMONUMENTATION

JAN 12 2001

SECTION

Register of Deeds Stamp & File Number

I, Jeffrey A. Bieszk, in a field survey on 6 Oct. 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

GLO set by Ziba Swan (1824)  
5" Elm N85E 15 lks  
5" Maple S07W 25 lks

Geo. Mark (1879) survey #830  
found Stone

Larry M. Gerschbacher LCRC  
L 552 P 27 and 28  
Found 3/4" iron bar  
Sign Post N40E 45.30 ft.  
Spike 12" Walnut N27W 48.05 ft.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" iron as witnessed by Gerschbacher. The iron was 2 feet West Road to the North in centerline Road East-West.. Dug and found nothing else. Accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 36" iron w/cap in Monument Box

Nail w/tag Post	S 10 E	22.46 ft.
Stop Sign	N 10 W	55.66 ft.
Nail w/tag 16" Walnut	N 15 W	48.41 ft.
Nail w/tag 6" Apple	N 25 E	67.65 ft.



Signed by *Jeffrey A. Bieszk*  
Surveyor's Michigan License No. 41093

Date OCTOBER 11, 2000