



LIBER 5 PAGE 29

034947

RECORDED
HILLSDALE CO. MICH.

00 OCT 11 AM 10:31

REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

HILLSDALE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 8S R 1W L-11

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Jeffrey A. Bieszk, in a field survey on 6 Oct. 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO set by Ziba Swan (1824)
46" B. Oak S82W 25 lks
10' W. Oak S51E 4 lks

Geo. Mark (1879) survey #830
24" Stone
20" Elm N17 3/4 E 100 lks
Stone S45E 35 lks

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Did not find any iron. Took proportionate measurement from K-11 to M-11, point landed 7 feet East of edge of Road. There fit occupation South being a field line. Dug and found nothing. Set corner at proportionate distance and accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 36" iron w/cap in Monument Box

Set witness iron w/cap	North	24.00 ft.
Set witness iron w/cap	East	20.00 ft.
Set witness iron w/cap	S 45 E	25.00 ft.
Set witness iron w/cap	S 45 W	42.00 ft.



Signed by [Signature]
Surveyor's Michigan License No. 41093

Date October 11, 2000