



REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

LIBER 3 PAGE 336

025218

RECORDED  
HILLSDALE CO. MICH.

NOV 20 AM 9:15

*Jeffrey A. Bieszk*  
REGISTERED

Register of Deeds Stamp & File Number

For corners in

HILLSDALE

(County)

Located In:

Corner Code #

1. Public Land Survey

T8S R 2W C-9

2. Property Controlling  
in Section

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Jeffrey A. Bieszk, in a field survey on 25 Oct., 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

GLO set by Wm. Brookfield. (1825)  
10" Whitewood North 14 lks.  
10" Beech S75.5W 17 lks.

Survey Donald Olmstead L1-P720  
Set iron

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found iron 6 feet South centerline of Camden Road. Match the measurement from measurements of Olmstead's survey. Olmstead set corner from survey done by R.J. Caryell 1889 survey # 1082. Dug and found no other evidence, accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 36" iron w/cap in Monument Box

Stop Sign	N 30 W	53.65 ft.
Stop Sign	S 10 E	44.85 ft.
Phone riser	N.50 W	52.05 ft.
Phone riser	S 50 W	49.30 ft.



Signed by *Jeffrey A. Bieszk*  
Surveyor's Michigan License No. 41093

Date 24 November 1999