



LIBER 5 PAGE 43

HILLSDALE COUNTY REMONUMENTATION CORNER
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

035812

HILLSDALE CO. MICH.

NOV -8 AM 8:45

REG. OF DEEDS

For corners in

HILLSDALE COUNTY
RANSOM TWP (County)

Located In:

Corner Code #

1. Public Land Survey T 8 S. R 2 W F-5
T R
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

SURVEY &
REMONUMENTATION

JAN 12 2001

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat SECTION

5. Private Claims

I, EDWARD W. REED, in a field survey on OCTOBER 2, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

QUARTER CORNER COMMON TO SECTIONS 9 & 16, RANSOM TOWNSHIP

A. Description of original monument and accessories and/or subsequent restoration:

1825: CORNER SET
1867: GEO. MARKS-STONE


B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

CORNER GONE DUE TO FARMING PRACTICES - NO FENCELINES OR OTHER SIGNS OF OCCUPATION
RESET CORNER MIDWAY AND ON LINE BETWEEN CORNERS EAST AND WEST
SET 3/4" X 30" REBAR IRON WITH REMON CAP AT GROUND LEVEL
SET CARSONITE MARKER ALONG SIDE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

3/4" X 30" IRON WITH REMON CAP WITH CARSONITE MARKER ALONG SIDE

TAG IN NORTH SIDE OF WOOD POST WEST 298.78'
CENTER OF 12" POPULAR N75W 305.7'
CENTER OF 8" WALNUT N98W 370.1'
TAG WEST SIDE POWER POLE N10W 386.05'
TAG WEST SIDE POWER POLE N27E 484.0'



AND IS ACCEPTED AS A CAREFUL AND FAITHFUL RE-ESTABLISHMENT
OF THE POSITION OF THE ORIGINAL CORNER.

Signed by EDWARD W. REED

Date OCTOBER 2, 2000

Surveyor's Michigan License No. 33985