

NOV 15 1994

## COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

JUL 6 8 15 AM '94

REGISTER OF DEEDS

Ingham County, Mich.

For corners in

INGHAM

(County)

Located In:

Corner Code #7

1. Public Land Survey	T 3N R 1W	G-11
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous	S T R	
Property in Sec.	S T R	

Register of Deeds Stamp &amp; File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, DAVID R. LOHR, in a field survey on APRIL 25, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													

## A. Description of original monument and accessories and/or subsequent restoration:

G-11 1. POST SET BY MUSGROVE EVANS IN DECEMBER 1826, WITNESSED BY:  
BEECH 6" SOUTH 46 DEGREES EAST, 4 LINKS (2.84')  
BEECH 22" SOUTH 33 DEGREES WEST, 24 LINKS (15.84')

2. MARGINAL NOTE MARKED "NEW" (NO DATE) WITNESSED BY:  
W. OAK 6" NORTH 16 DEG. 60 1/2 LINKS (43.89')  
SUGAR 5" SOUTH 80 1/2 DEG. EAST 434 LINKS (286.44')  
CONTINUED ON BACK

## B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-11

FOUND MONUMENT IN MON. BOX (NO COVER) AS PER LCRC L5, PG.221.  
TOP OF MONUMENT BROKEN OFF ABOUT 6" AND RE-BAR BENT.  
DID NOT EXCAVATE INTERIOR OF MON. BOX DUE TO PREVIOUS EXCAVATION  
COMPLETED IN 1979. ACCEPTED MONUMENT AS LOCATION OF CORNER.

## C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-11 - 4" CONCRETE MONUMENT IN MON BOX


SET N/T #30090 IN E/S P. POLE	AZ. 350 DEG.	74.18'
SET N/T #30090 IN S/S TW. 16" BL. WALNUT	AZ. 83 DEG.	222.55'
SET N/T #30090 IN N/S 24" MAPLE	AZ. 104 DEG.	157.45'
SET N/T #30090 IN NE/S POST	AZ. 124 DEG.	58.12'
NE COR WHITE BARN	AZ. 184 DEG.	160.68'
NW COR WHITE BARN	AZ. 221 DEG.	219.31'
BEARING AND DISTANCE TO G-10	AZ. 00-00-03	2665.46'

Signed by

David R. Lohr

Date JUNE 28, 1994

Surveyor's Michigan License No. 30090

P.A. 345 INGHAM COUNTY  
PEER APPROVED 5/11/94 RCFORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS 26, 1981  
REVISED JAN 1987

Page 2

## G-11 CONTINUED

3. RECORDED SURVEY BY A.P. DRAKE DATED APRIL 22, 1877 VOLUME 3, PAGE 132.  
"STONE" WITNESSED BY: W. OAK 6" N 16 DEG. E, 66 1/2 LKS. (43.89')  
6" SUGAR S 16 DEG. E, 66 LINKS (43.56')
4. UNRECORDED SURVEY IN FOLDER #1, PG.63 BY T.J.BROWN DATED MAY 17, 1893,  
NO MENTION OF MONUMENT, WITNESSED BY:  
W.OAK 16" NORTH 16 DEGREES EAST, 66 LINKS ( 43.89')  
SUGAR 16" SOUTH 80 1/2 DEGREES EAST, 433 1/2 LINKS (286.11')
5. RECORDED BY W.A. ROWE, COUNTY SURVEYOR, IN 1896, RECORDED IN VOL.2,  
PAGE 250, REFERS TO "STONE", WITNESSES SAME AS #4 ABOVE.  
  
W.OAK 16" NORTH 16 DEGREES EAST, 66 LINKS ( 43.56')  
SUGAR 16" SOUTH 80 1/2 DEGREES EAST, 433 1/2 LINKS (286.11')
6. RECORDED SURVEY BY W.A. ROWE, COUNTY SURVEYOR DATED APRIL 14-16 1896,  
VOLUME 3, PAGE 238, REFERS TO "STONE", WITNESSED AS #4 ABOVE.
7. UNRECORDED SURVEY IN FOLDER #1, PG.63 BY T.J.BROWN DATED MAY 17, 1893,  
NO MENTION OF MONUMENT BUT WITNESSED AS #3 ABOVE.
8. UNRECORDED SURVEY IN FOLDER #1, PG.1 BY E.A.CALKINS DATED FEB 20, 1901,  
NO MENTION OF MONUMENT BUT WITNESSED BY:  
W.OAK 6" NORTH 16 DEGREES EAST, 66 1/2 LINKS ( 43.89')  
SUGAR 5" SOUTH 80 1/2 DEGREES EAST, 434 LINKS (286.44')
8. NO OTHER REFERENCES FOUND IN COUNTY SURVEYORS RECORDS
9. LCRC BY RONNIE M. LESTER, PS #18998, DATED 4/4/79, LIBER 5, PG. 221  
  
"EXCAVATED A 6.5' X 10.4' HOLE TO AN AVERAGE DEPTH OF 1.9',  
MOSTLY NORTH OF THE CENTERLINE OF HARPER ROAD. FOUND RAILROAD  
SPIKE AT ROAD SURFACE, ON THE CENTERLINE OF HARPER ROAD AND  
62' WEST OF FENCE LINE SOUTH. FOUND 3" X 7" X 9" FLAT STONE  
SURROUNDED AND SUPPORTED BY BRICK AND CROCKERY 0.75' BELOW  
ROAD SURFACE IN DARK CLAY, ON THE CENTERLINE OF HARPER ROAD  
AND + 47.5' WEST OF FENCE LINE SOUTH. MEASURED WEST 2660'  
TO F-11 AND EAST 2650' TO H-11 IN CLOSE ACCORD WITH G.L.O.  
DISTANCES. ACCEPTED STONE FOR CORNER DESCRIBED BY DRAKE IN  
SURVEY NOTED ABOVE." EXCAVATION CONDUCTED BY INGHAM COUNTY  
SURVEY AND REMONUMENTATION PROJECT CREW.  
  
"SET 4" X 36" CONCRETE MONUMENT WITH 1/2" X 38" REROD AND CAP  
#18998 WITH CONCRETE COLLAR AND COVER AT LOCATION OF STONE  
DESCRIBED ABOVE:" WITNESSED BY:  
NAIL/TAG, #18998, N/S 28" MAPLE, ESE, 157.45'  
NAIL/TAG, #18998, 8" TWIN OAK, ENE, 22.35'  
NE CORNER OF CONC. FOUND. OF E. WHITE BARN SSW, 160.42'  
NE CORNER OF CONC. FOUND. OF W. WHITE BARN, SW, 219.25'