## REMONUMENTATION

OCT 07 1993

## REMONUMENTATION CORNER

## COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

	্র	ALCEN FOR
Daine M. Olans	SEP 21	ECEIVED FO
	P3:24	DNIA COUNTY IVEO FOR RECORD

	or corners in  Lonia (County)	Located In:	Corner Code ##	POR RECU
1.	Public Land Survey	T R	<u>K-9</u>	P3:24 P3:24 CEDS
2.	Property Controlling	S R		
	in Section	S T R		
3.	Miscellaneous	S T R		Register of Deeds Stamp & File Number
	Property in Sec.	S T R		
4.	Lot No,	Recorded Plat		——— ABCDEFGHIJKL
5.	Private Claims			
	ν,			2 6 5 4 3 2 1
				4 7 8 9 9 10 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	Marinue Mulder	, in a field survey onAugu	igt 9 19 03	. 5 1 1 1 1 1
		equirements of P.A. 74. Michigan P.A.		

in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

10 11 12

A. Description of original monument and accessories and/or subsequent restoration:

THis corner was first set by U.S. Deputy Surveyor John Mullett, April 25 to August 7, 1831. He calls for the corner to be a 12" Lynn Tree, but had no witnesses. Perpetuation: D.C. Crawford former Ionia County Surveyor performed a sectional survey of Section 23, October 28 & 29 of 1888 found in Volumn 1 page 456 Ionia County Survey records he does not state what he set. His witnesses are: (1) 12" Maple N 31° E 1.88  $\frac{1}{2}$  chains (2) 6" Maple S 33° W 71 links

B. Description of corner evidence-found and/or method applied in restoring or reestablishing corner: No witness trees remain. Excavated road bed with a backhoe and at an approximate depth of 30" found stone with smaller stones at base in line with East-West fence. Accepted as a careful and faithful perpetuation of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Set 3/4" x 36" steel bar with a 2 3/4" cap stating "Ionia County P.S. 25863" next to stone with the following witnesses:

Nail & tag 16" Hickory N 21° W 47.08' Nail & tag 14" Maple N 44° W 43.28' Nail & tag 16" twin Elm S 38° W 24.72' Nail & tag 24" Oak N 84° E 31.00'

LIBER 003 PAGE 32

Signed by Mar C Mulle	Date August 30. 1993
Surveyor's Michigan License No. 25863	SORM APPROVED BY MICHIGAN STATE HOARD OF LAND SHRVEYORS, IAN. 28, 197