

SURVEY & REMONUMENTATION

OCT 07 1993

REMONUMENTATION CORNER

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Ionia

(County)

Located In: Sec. 21 Corner Code #

- | | | |
|------------------------------------|-----------|-----|
| 1. Public Land Survey | T 6N R 5W | G-9 |
| | T R | |
| | T R | |
| | T R | |
| 2. Property Controlling in Section | S T R | |
| | S T R | |
| 3. Miscellaneous | S T R | |
| Property in Sec. | S T R | |

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

STATE OF MICHIGAN
IONIA COUNTY
RECEIVED FOR RECORD
93 SEP 21 P 3:23
Olive M. Adams
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

I, Marinus Mulder, in a field survey on June 25, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
Corner first set by U.S. Deputy Surveyor, Lucious Lyon who later became one of Michigan's first State Senators. Set post witnessed by (1) 14" White Oak N14°E 14 links (2) 10" Lynn S 30°E 20links. This corner was perpetuated by Captain D.C. Crawford, Civil war veteran and former Ionia County Surveyor in 1890, when he remonumented Portland Township. Crawford has marginal witness notes on a copy of the G.L.O. notes: He states 6" White Oak N12°E 42 Links; 10" White Oak S41°E 59 1/2 Links. Crawford also has another set of witnesses in 1895: 6" Hickory N5°W 37 links; 8" Hickory S20°E 50 1/2 links. Professional Surveyor, Clyde Stephens #3829 recorded this corner stating he found a railroad spike recorded in Liber 1 page 43, Feb. 11, 1972. Douglas Bonnema P.S.#12579 also recorded this same point August 16, 1973 (see back)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
One of Crawford's 1895 witness trees remain. Found 1" solid shaft-not a railroad spike. Removed shaft and excavated road bed to a depth of 30". To our frustration, found no clay cylinder which Crawford used for his remonumentation. Shaft was close to Crawford's witness distance of 1895 from the 6" Hickory. Accepted this position as a faithful perpetuation of the position of the original corner.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
Set 3/4" x 36" steel rod with 2 3/4" cap stating "Ionia County P.S. 25863"

Witnesses:
Nail & tag 28" Hickory North 23.02' (Crawford's 1895 witness)
Nail & tag 18" Hickory N57°W 42.65'
Nail & tag 18" Hickory S50°W 45.64'
Nail & tag 12" Hickory S40°E 28.48'

LIBER 003 PAGE 23

Signed by Marinus Mulder Date August 30, 1993

Surveyor's Michigan License No. 25863

filed 10/11/93

A: (con't) recorded in Liber 1 page 82.

SURVEY &
REMONUMENTATION

OCT 07 1993

COMMISSION