

REMONUMENTATION

DEC 8 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

LIBER 003 PAGE 347

For corners in IONIA Located In: _____ Corner Code # _____
(County)

1. Public Land Survey T7 N R8 W K-3 _____
T _____ R _____
T _____ R _____
T _____ R _____

2. Property Controlling S _____ T _____ R _____
in Section S _____ T _____ R _____

3. Miscellaneous S _____ T _____ R _____
Property in Sec. S _____ T _____ R _____

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

STATE OF MICHIGAN
IONIA COUNTY
RECEIVED FOR RECORD
12 NOV 97 3:47 P.M.
DIANE H. ADAMS
Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, MARINUS MULDER, in a field survey on SEPTEMBER 18 1997, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
THIS CORNER WAS FIRST ESTABLISHED BY U.S. DEPUTY SURVEYOR NOAH BROOKFIELD IN 1837. A WOOD POST WAS SET WITNESSED BY A 18" BEECH S11°W 16 LINKS AND A 10" BEECH N67°W 27 LINKS.

PERPETUATION: A.C. SMITH FORMER COUNTY SURVEYOR PERFORMED A SURVEY OF SECTION 1, T7N-R8W, JUNE 1875, RECORDED IN VOLUME 1, PAGE 118 OF IONIA COUNTY SURVEY RECORDS. SMITH NOTED THAT STONES MARKED THE POSITION OF K-3.

THE IONIA COUNTY ROAD COMMISSION IMPROVED HAWLEY HIGHWAY IN 1959. THE COUNTY ROAD COMMISSION WITNESSES FOR K-3 FOUND ON THE SECTION CORNER INDEX MAP IS: "P.K. NAIL" & TAG WITNESSED BY TELEPHONE POLE N.W. 36.25 FEET; SIGN POST S.W. 24.50 FEET.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
AT THE INTERSECTION OF HAWLEY HIGHWAY AND ELLISON ROAD FOUND A NAIL & TAG UNDER THE ROAD SURFACE. EXCAVATED BELOW NAIL & TAG AND FOUND A SLIM POINTED STONE ABOUT 16" LONG. EXCAVATED BELOW STONE, BUT FOUND NO OTHER EVIDENCE. ACCEPTED THIS AS THE PERPETUATED CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
SET A 24" MONUMENT WITH A 4" DIAMETER CAP STAMPED "IONIA COUNTY-25863" IN PLACE OF THE EXISTING MONUMENTATION WITNESSED BY:
NAIL & TAG WEST SIDE POWER POLE S34°E 103.57 FEET
TOP CENTERLINE M.B.T. RISER BOX N37°E 57.28 FEET
CENTERLINE 2 1/2" STEEL POST N16°E 86.24 FEET
NORTH EDGE STOP SIGN S66°W 34.66 FEET
CENTERLINE HAWLEY HIGHWAY 1.5 FEET WEST

Signed by Marinus A. Mulder Date 11-12-97
Surveyor's Michigan License No. 25863

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1975
REVISED JAN. 1983
ADAPTED FOR WORD PROCESSING MARCH, 1993



Ratified by Peer Group
P.A. 345 Ionia County

Date 10-20-97
Marinus A. Mulder, Chairman