' SURVEY & REMONUMENTATION

APR 27 1995

COMMISSION

___ , Recorded Plat __

IOSCO COUNTY REMONUMENTATION CORNER LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN IOSCO COUNTY FILED

5 DEC 94 1:54 P.M.

Ю	r corners in		
	Tosco (County)	Located In: Corner Code ##	
1.	Public Land Survey .	T R T R T R T R T R T R	
2.	Property Controlling in Section	S 30 T 22N R 8E A-10 to A-11 S T R	
3.	Miscellaneous Property in Sec.	S T R S T R	

BONITA N. COYLE REGISTER OF DEEDS

94-23

Register of Deeds Stamp & File Number

James H. Granger, in a field survey on September 19 94	
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned	
n lines 1 and 2 above were in conformance with regulations and rules therefore as required in the	
current manual of survey instructions of the United States Department of the Interior, Bureau of Land	
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5	
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a	
Court of Law; established, re-established, monumented, re-monumented, recovered, found as	

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

10

1843 Original Survey

Cor. falls in River - no M.C. set

John Mullett

1887 Sub'd

5. Private Claims _

expressed below:

King's 3rd Add'n to Tawas City

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Located ex. cor. at A-10 and A-9 to establish W. Twp. line. Located S_4^1 of Sec. 25, T22N, T7E and monuments in King's Sub'd to establish S. line of Sec. 25. Extended both lines & intersected in River as called for in original notes. Distances both ways agree with original notes. Set witness corner on N. bank of River on W. Twp. line 254.76 N. of cor. position.

> ACCEPTED BY THE IOSCO COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER P.A. 345 OF 1990 AT A MEETING HELD ON /1-10-94

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set $5/8" \times 30"$ rebar with alum. cap 520 $^{\circ}W$ 21.48' Set tag in Power Pole s45°W 120.38' Set tag in Power Pole N70°W 96.81' Set tag in Power Pole N25°W 106.15' S.W. cor of church



Surveyor's Michigan License No. .

November 10,

__ Date _

1994