

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Iosco

(County)

Located In

Corner Code #

witness
corner to
I-4

1. Public Land Survey

T 24N R 8E I-4-N
T 24N R 8E I-4-S

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous
Property in Section

S T R
S T R

Register of Deeds Stamp & File Number

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on May 29, 2007 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

I-4 G.L.O. J. Mullett and Wm. Burt 1843 set quarter section post

Wit: W. Pine 10" S57°E 19 links
W. Pine 10" N52°E 22 links

Michigan Consolidated Gas construction survey and map shows monument for corner. No witnesses were given.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

I-4-N Corner I-4 falls in an active Beaver Dam. A corner position was calculated per Michigan Consolidated Gas R.O.W. Map. A Witness Corner was set on the section line 60.00' North of the calculated West ¼ corner of section 11.

I-4-S Corner I-4 falls in an active Beaver Dam. A corner position was calculated per Michigan Consolidated Gas R.O.W. Map. A Witness Corner was set on the section line 130.00' South of the calculated West ¼ corner of section 11.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-4-N Set a 5/8" x 32" Rerod with P.S. Cap #33981 60.00' North of the calculated corner I-4.

I-4-S Set a 5/8" x 32" Rerod with P.S. cap #33981 130' South of the calculated corner I-4.

Wit: 12" Maple S15°W 26.62'
6" Maple N85°W 25.19'
4" W. Pine N50°W 51.45'
8" W. Pine N27°W 42.15'
Waters Edge South 40'

Wit: 14" Maple N35°W 14.99'
4" W. Pine N49°E 20.93'
15" Maple S12°W 15.43'
15" W. Pine N76°W 23.75'
Waters Edge North

Signed by:

Carl T. Kiiskila

Date:

6-25-07

Surveyor's Michigan License No.:

33981

