

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

FEB 15 2001

SECTION

For corners in IOSCO Located in: \_\_\_\_\_ Corner Code # \_\_\_\_\_

1. Public Land Survey T 24N R 9E M.C. I-J3 #10  
 T \_\_\_\_\_ R \_\_\_\_\_  
 T \_\_\_\_\_ R \_\_\_\_\_  
 T \_\_\_\_\_ R \_\_\_\_\_  
 T \_\_\_\_\_ R \_\_\_\_\_  
 2. Property Controlling S \_\_\_\_\_  
 in Section S \_\_\_\_\_  
 T \_\_\_\_\_ R \_\_\_\_\_  
 T \_\_\_\_\_ R \_\_\_\_\_  
 3. Miscellaneous S \_\_\_\_\_  
 Property in Sec. \_\_\_\_\_  
 \_\_\_\_\_  
 4. Lot No. \_\_\_\_\_ Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, WILLIAM E. WOODS P.S., in a field survey on OCT. 16, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1843: ORIGINAL GOVERNMENT NOTES

SET POST 12.39 CHAINS EAST OF I-3

W. PINE 14" S44°W 18 LKS.

W. PINE 16" N57°W 96 LKS

ACCEPTED BY THE IOSCO COUNTY  
SURVEY PEER GROUP AS THE  
OFFICIAL CORNER UNDER P.A.  
345 OF 1990 AT A MEETING  
HELD ON 10-11-2000

*James H. Branger*

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1946: ORA F. GOULD

LAKE HURON SAND BEACH SUBDIVISION PLAT SHOWS  
NORTHEAST CORNER OF SECTION 10, BUT NO SECTION  
LINE GOING EAST FROM CORNER

2000: WILLIAM E. WOODS

MEASURED EAST PARALLEL WITH SOUTH BOUNDARY OF LAKE  
HURON SAND BEACH SUBDIVISION 12.39 CHAINS 817.44 FEET  
DISTANCE FELL 220 FEET (PLUS OR MINUS) WEST OF WATERS  
EDGE OF LAKE HURON

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

5/8" BAR &amp; REMON CAP MEANDER CORNER

POPLAR 4" N7°E 15.46 NAIL &amp; TAG

S.W. CORNER CONCRETE BLOCK FOUNDATION HOUSE #7456 N50°W 46.95'

N. E. CORNER CONCRETE BLOCK FOUNDATION HOUSE #7452 S80°W 22.48'

N. E. CORNER CONCRETE BLOCK FOUNDATION HOUSE #7452 S33°W 19.65'

Signed by

*William E. Woods*

WILLIAM E. WOODS P.S.

Surveyor's Michigan License No. 25882

Date

12-06-2000

