

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S 16 T 43N R 31W	6
	S 16 T 43N R 31W	8
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 07/01/2008 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(6-Sec. 16) Northeast 1/16 corner, Section 16. Not established in the original survey.

(8-Sec. 16) West 1/16 corner, Section 16. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(6-Sec. 16) Established the corner at the intersection of straight lines connecting opposite 1/16
corners.

(8-Sec. 16) Established the corner midway and on a straight line between Center of Section 1312.50'
east and Quarter corner 1312.5' west.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(6) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
4" Balsam N46E 24.5' mrkd "1/16S BT"
15" Cedar S36E 42.2' do
3" B.Spruce West 15.2' do
6" Maple in clump N32W 23.1' do
Set cedar post adjacent. Bearings are magnetic.

(8) Set 1"IDx32" I.pipe with 4" alum. MDNR cap
made firm in a mound of rock 1.5' dia. x 1' high.
Set measuring nail with MDNR tag in the side of:
5" Sugar N63E 21.6' mrkd "1/16S BT"
9" Cedar S09E 20.0' do
7" Cedar S43W 6.3' do
5" Cedar N65W 6.55' do
Set cedar post adjacent. Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 07/14/2008

For the Michigan Department of Natural Resources, Office of Land and Facilities

