

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron	Located In:	Corner Code #
(County)		
1. Public Land Survey	T R	
	T R	
	T R	
	S 19 T 43N R 33W	B8
2. Property Controlling	S 19 T 43N R 33W	11
in Section	S T R	
3. Miscellaneous	S T R	
Property in Sec.	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File
Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski , in a field survey on Jan 29 , 2008 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(B8) Center of Section 19. Not established in the original survey.

(11-Sec. 19) Southwest 1/16 corner, Section 19. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(B8) Established the corner at the intersection of straight lines connecting opposite 1/4 corners.

(11-Sec. 19) Established the corner at the intersection of straight lines connecting opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(B8) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
8" Sugar N73E 12.8' mrkd "C1/4 BT"
4" Sugar S03W 2.3' do
6" Sugar N76W 9.8' do
5" Sugar N22W 6.8' do
Set sq'd post adjacent. Bearings are magnetic.

(11) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
6" Sugar N55E 10.3' mrkd "1/16S BT"
6" Sugar S52E 12.0' do
4" Sugar S60W 17.5' do
4" Sugar N43W 12.9' do
Set sq'd post adjacent. Bearings are magnetic.

Signed by

Stephan J. Szyszkoski



Date

2/5/08

Surveyor's Michigan License No.

33986

For the Michigan Department of Natural Resources, Office of Land and Facilities

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS