

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>Iron</u>	Located In:	Corner Code FS
(County)		
1. Public Land Survey	T <u>44N</u> R <u>31W</u>	<u>FS</u>
	T _____ R _____	<u>FS</u>
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S <u>16</u> T _____ R _____	<u>2</u>
	S <u>17</u> T _____ R _____	<u>1</u>
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

92

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
 5. Private Claims _____

I, Kath Sackett, in a field survey on June 14, 19 89, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													

A. Description of original monument and accessories and/or subsequent restoration:

BS	FS	2	1
Original monument and accessories not found.	Original monument and accessories not found.	Not set on original survey nor subsequently, apparently.	Not set on original survey nor subsequently, apparently.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

BS	FS	2	1
Restored midway and on line.	Restored midway and on line.	Established midway and on line.	Established midway and on line.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

BS	FS	2	1
Set 1" x 3/8" IP with 4" aluminum cap.	Set 1" 10 x 32" IP with 4" aluminum cap.	Set 1" 10 x 32" IP with 4" aluminum cap.	Set 1" x 32" IP with 4" aluminum cap.
9" sugar 808E 5.2' 1/48 NBT	5" maple 809W 11.7' 1/48 NBT	5" maple 822E 20.1' 1/168 BT	6" sugar 826W 15.6' 1/168 BT
7" sugar 848W 7.2' 1/48 NBT	4" maple 859W 19.0' 1/48 NBT	7" white birch 879W 16.4' 1/168 BT	6" sugar 882W 11.5' 1/168 BT
5" sugar 910W 6.3' 1/48 NBT	10" balsam 845E 41.3' 1/48 NBT	8" spruce 850E 36.2' 1/16 BT	10" ash 870E 26.0' 1/168 BT
10" dead cedar signature tree w/tag 845W 35.4'		10" aspen 854E 2.9' squared	

Signed by


Kath Sackett

Date

9-21-89

Surveyor's Michigan License No.

19006



FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 29, 1971
 REVISED MAY 14, 1976
 REVISED JAN., 1983