

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 8 T 44N R 31W	11
	S 8 T 44N R 31W	10
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on 11 09/20/2011 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established,  
monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(11-Sec. 8) Southwest 1/16 corner. Not previously monumented.

(10-Sec. 8) South 1/16 corner between Sections 7 and 8. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(11-Sec. 8) Established the position for the corner at the intersection of straight lines connecting  
opposite 1/16 corners.

(10-Sec. 8) Established the position for the corner midway and on the Section line between Quarter  
corner 1334.15' north and Section corner 1334.15' south. The corner falls in a large open grass  
marsh, extending to the west and south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(11) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
12" Maple N80E 36.1' mrkd "1/16S BT"  
11" Cedar S01E 44.8' do  
9" Hemlock S39W 16.15' do  
13" Hemlock N68W 13.25' do  
Set sq'd Cedar post adjacent.  
Bearings are magnetic.

(10) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
8" Tamarack N15E 63.2' mrkd "1/16S BT"  
3" Tamarack N27E 68.9' do  
4" Tamarack N1W 80.6' do  
Set sq'd Cedar post adjacent.  
Bearings are magnetic.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 01/19/2012

For the Michigan Department of Natural Resources, Forest Management Division

