

SURVEY & REMONUMENTATION

JAN 13 1998

SECTION

IRON COUNTY
MICHIGAN
RECEIVED FOR RECORD

97 DEC 23 PM 1:26

L.C. Records L. 7 P. 121

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

REGISTER OF DEEDS

For corners in

<u>Iron</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>44N</u> R <u>32W</u>	<u>C-3</u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
2. Property Controlling in Section	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
3. Miscellaneous Property in Sec.	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

Section Corner Sec. 5,6,7,8, T44N, R32W

I, Gary L. Pisoni, in a field survey on November 3, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6	5	4	3	2	1						
3													
4		7	8	9	10	11	12						
5													
6		18	17	16	15	14	13						
7													
8		19	20	21	22	23	24						
9													
10		30	29	28	27	26	25						
11													
12		31	32	33	34	35	36						
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established in July of 1849 by Zelotes B. Searls, U.S. Deputy Surveyor.

Original Corner; Sugar Post
Original Bearing Trees:

Fir	10"	S20° W	14 links (9.24 feet)
Hemlock	18"	N30° E	20 links (13.20 feet)

On 9-16-71, Arthur O. Enger, RLS with the Michigan Dept. Of Natural Resources, restored the corner position using record distances from corners 1 mile North and 1 mile West, which agrees with natural feature ties. Set a 4 inch diameter aluminum capped pipe monument, 3 feet long, 10 inches above the ground. Recorded in Land Corner Certificate L. 1, Pages 191-192, on June 27th, 1973.

1971 Bearing Trees;

W. Spruce	6"	N23° W	8.4 feet
Balsam	5"	N29° E	13.0 feet
Balsam	5"	S25° E	3.5 feet

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of original B.T.s found.

On 11-3-97 found the monument as set by Arthur O. Enger and the following bearing trees;

W. Spruce	13"	N26° W	8.70 feet
Balsam	11"	N29° E	13.29 feet
Balsam	11"	S28° E	3.73 feet

Corner record research on file with County Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Blazed and scribed the following new bearing trees: (All measurements taken to a nail in side of tree)

White Spruce	7"	N73° W	53.85 feet
Steel Sign Post		N46° E	0.87 feet

PEER GROUP APPROVED

Gary L. Pisoni 11-11-97
IRON COUNTY REPRESENTATIVE

97-16

Signed by Gary L. Pisoni

Date November 7, 1997

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN. 1983
REVISED OCT., 1995