

SURVEY &
REMONUMENTATION

JAN 13 1998

SECTION.

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

IRON COUNTY
MICHIGAN
RECEIVED FOR RECORD

97 DEC 23 PM 1:30
L.C. Records L.P. 159

Gilbert Stiles
REGISTER OF DEEDS

For corners in

Iron
(County)

Located in:

Corner Code #

1. Public Land Survey

T 44N R 32W

C-8

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

Quarter Corner Section 19 and 20, T44N, R32W

I, Gary L. Pisoni, in a field survey on December 2, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original Corner established in 1849 by Zelotes B. Searls, U.S. Deputy Surveyor.
Original Corner: Cedar Post
Original Bearing Trees:

Cedar	8"	S 70° E	6 lks. (3.96 feet)
Cedar	8"	N 75° W	28 lks. (18.48 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original corner evidence was recovered.

Set the quarter corner by single proportionate measurement on line between the Northeast and Southeast Section corners of Section 19.

Corner record research on file with County Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position, set a 3/4" outside diameter aluminum rod monument, 4 feet long, 4" above the ground surface with a 3" dia. aluminum cap stamped as follows: Iron County Remonumentation, T44N, R32W, 1/4, S19, S20, 1997, RLS 27457. Blazed and scribed the following new bearing trees: (Measurements are taken to a nail in side of tree)

Cedar	10"	N 48° E	22.89 feet
Cedar	12"	S 22° E	31.60 feet
Cedar	7"	S 54° W	16.78 feet
Cedar	8"	N 30° W	10.24 feet
Steel sign post		S 80° W	0.60 feet

97-26a

Signed by Gary L. Pisoni

Date December 16, 1997

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN 28, 1971
27457
REVISED MAY 19, 1975
REVISED JAN., 1983
REVISED OCT., 1995

PEER GROUP APPROVED
Gary L. Pisoni 12-19-97
IRON COUNTY REPRESENTATIVE

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

