

SURVEY & REMONUMENTATION

JAN 13 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>Iron</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>44N</u> R <u>32W</u>	<u>E-3</u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
2. Property Controlling in Section	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
3. Miscellaneous	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
Property in Sec.	S <u> </u> T <u> </u> R <u> </u>	<u> </u>

IRON COUNTY
MICHIGAN
RECEIVED FOR RECORD
97 DEC 23 PM 1:26
L.C. Records L.7 P.117
Gary L. Pisoni
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

Section Corner Sec. 4,5,8,9, T44N, R32W

I, Gary L. Pisoni, in a field survey on November 3, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by Zelotes B. Searls, U.S. Deputy Surveyor, in July 1849.
Original Corner: Cedar Post
Original Bearing Trees:

Cedar	12"	S21° W	24 links(15.84 feet)
Cedar	12"	N73° E	22 links(14.52 feet)

On 10-11-71, Arthur O. Enger, RLS with the Michigan Dept. Of Natural Resources, restored the corner using natural feature ties and record distance measurements from 1 mile to the North and 2 miles to the West. Set a 4" diameter aluminum capped pipe monument, 3 feet long and 12" above the ground. Recorded in Land Corner Certificate L. 1, Pages 189-190, on June 27th, 1973.

1971 Bearing Trees:

Cedar	10"	S83° W	9.2 feet
Cedar	6"	N67° E	11.5 feet
Cedar	8"	N10° W	7.2 feet

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of original B.T.s found.

On 11-3-97 found monument as set by Arthur O. Enger, and the following bearing trees;

Cedar	13"	S84° W	9.62 feet
Cedar	11"	N06° W	7.55 feet
Cedar	9"	N67° E	11.74 feet

PEER GROUP APPROVED

Gary L. Pisoni 11-11-97
IRON COUNTY REPRESENTATIVE

Corner record research on file with County Representative

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Blazed and scribed the following new bearing trees: (All measurements taken to a nail in side of tree)

Spruce	11"	S50° E	23.94 feet
Steel Sign Post		N40° E	0.95 feet

97-12
Signed by *Gary L. Pisoni* Date November 7, 1997

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN 28 1997
REVISED MAY 14 1975
REVISED JAN. 1983
REVISED OCT. 1990

