

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 7 T 44N R 32W B4	
	S 7 T 44N R 32W 12	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4					8		9		10		11		12
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 12 02/03/2010 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(B4) Center of Section 7. Not established in the original survey.

(12-Sec. 7) South 1/16 corner, Section 7. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(B4) Established the corner at the intersection of straight lines connecting opposite 1/4 corners.

(12-Sec. 7) Established the corner midway and on a straight line between Center of Section 1319.80'
north and Quarter corner 1319.80' south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(B4) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
7" Poplar N33E 4.9' mrkd "C1/4 BT"
8" Sugar S50E 22.65' do
7" Sugar S04E 10.1' do
12" Sugar S41W 16.5' do
Set sq'd post adjacent. Bearings magnetic.

(12) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
8" Poplar N25E 4.4' mrkd "1/16S BT"
6" twin Sugar S86E 6.2' do
3" Y.Birch S43E 17.8' do
4" Sugar N80W 21.5' do
Set sq'd post adjacent. Bearings magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 02/04/2010

For the Michigan Department of Natural Resources, Office of Land and Facilities

