

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

Iron County

FOR CORNERS OF—	LOCATED IN—	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 45 ^{N.} _{XX} R. 32 ^{XX} _{W.}	C 6
2. PROPERTY CONTROLLING IN SECTION 17	T. 45 ^{N.} _{XX} R. 32 ^{IX} _{W.}	3, 10
3. MISCELLANEOUS PROPERTY IN SECTION	T. ^{N.} _{S.} R. ^{E.} _{W.}	
4. LOT NO.	RECORDED PLAT	
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 12-9-83, 1983, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 12-9-83, 1983, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner A6: Original monument and accessories not found
 Corner 3: Not set on original survey nor subsequently apparently.
 Corner 10: Not set on original survey nor subsequently apparently.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner C6: Restored midway and on line between section corners north and south.
 Corner 3: Established midway and on line between section corner north and 1/4 corner south.
 Corner 10: Established midway and on line between section corner south and 1/4 corner north.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner C6: Set 1" ID by 32" I.P. w/ 4" alum. cap. 5" Spruce S78W 8.0 ft. 1/4S, NBT 5" Spruce N45E 34.9 ft 1/4S, NBT 5" Spruce N04W 40.8 ft 1/4S, NBT	Corner 10: Set 1" I.D. by 32" I.P. w/4" alum. cap. 8" Spruce N72E 10.6 ft 1/16S, BT 6" Spruce S44W 12.8 ft. 1/16S, BT 6" Spruce S28E 11.4 ft. 1/16S, BT
Corner 3: Set 1" ID by 32" I.P. w/4" alum. cap. 14" Spruce S02E 30.7 ft. 1/16S, BT 14" Spruce N38W 12.5 ft 1/16S, BT 14" Spruce N74E 16.2 ft. 1/16S, BT	

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE _____

MICHIGAN REGISTERED LAND SURVEYOR

Keith L. Sackett

Michigan Department of Natural Resources

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006