

# SURVEY & REMONUMENTATION

FEB 21 2001

## SECTION

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Iron  
(County)

Located In:

Corner Code #

1. Public Land Survey

T 44N R 37W

C-1

T 45N R 37W

C-13

T      R     

T      R     

2. Property Controlling  
in Section

S      T      R     

S      T      R     

3. Miscellaneous

S      T      R     

Property in Sec.

S      T      R     

4. Lot No.         , Recorded Plat         

5. Private Claims         

Section Corner to Sections 31 and 32, T45N, R37W

Section Corner to Sections 6 and 5, T44N, R37W

I, Gary L. Pisoni, in a field survey on October 18, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE:** Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established on June 9, 1847 by John Burt, U.S. Deputy Surveyor.

Original Corner; Sugar Post

Original Bearing Trees:

Yellow Birch	16"	N 70° W	8 links (5.28 feet)
Sugar	15"	N 30° E	14 links (9.24 feet)

On 7/16/1851, E.L. Martin, U.S. Deputy Survey, made the following new bearing trees:

Yellow Birch	10"	S 14° E	48 links (31.68 feet)
Yellow Birch	14"	S 43° W	33 links (21.78 feet)

In 1946, G.A. Shadko, RLS restored the corner position with a 4" diameter concrete monument with a brass cap stamped as follows: Michigan Conservation Department, Public Fishing Site, T45N, R37W, S-31, S-32, S-5, S-6, T44N, 1946, G.A. Shadko

In 1982, John H. Fisher, RLS recovered the above monument and established the following new bearing trees:

Red Maple	8"	N 21° E	30.75 feet
Red Maple	5"	N 61° W	22.90 feet
Balsam	7"	S 9° E	13.53 feet
Steel sign post		N 85° E	1.80 feet

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of original B.T.s found.

Found monument as described above and the following bearing trees:

Red Maple (dbl)	12"	N 18° E	30.78 feet
Steel sign post		N 83° E	1.8 feet

Monument is 12" above ground surface.

Corner record research on file with County Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Blazed and scribed the following new bearing trees: (All measurements taken to a nail in side of tree)

Oak	12"	N 73° E	26.11 feet
Sugar Maple	7"	S 19° W	8.43 feet
Yellow Birch	8"	N 56° W	16.27 feet

00-033

Signed by Gary L. Pisoni

Date 11-13-2000

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1995

LIBER 8 PAGE 265

COMMENCING YEAR 2000  
RECEIVED FOR RECORD  
IRON COUNTY, MICHIGAN

00 DEC -8 PM 1:05

L.P. Records: L. 8, P. 265

*Gary L. Pisoni*  
REGISTERED LAND SURVEYOR

Register of Deeds Stamp & File Number

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

PEER GROUP APPROVED

*Gary L. Pisoni 11-30-2000*

COUNTY REPRESENTATIVE

