

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 30 T 46N R 33W	3 (GCDB 100260)
	S 29 T 46N R 33W	13 (GCDB 260220)
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on 06/01/15 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(3-Sec. 30) North 1/16 corner between Section 30 T46N-R33W and Section 25 T46N-R34W. Not previously monumented.

(13-Sec. 29) Southeast 1/16 corner, Section 29. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(3-Sec. 30) Established the position for the corner midway and on the Range line between Quarter corner 1319.14' south and Section corner 1319.14' north.

(13-Sec. 29) Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(3) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
22" Sugar N83°E 3.95' mrkd "1/16S BT"  
5" B.Spruce S34°W 28.7' do  
4" B.Spruce S66°W 26.95' do  
14" Sugar N06°W 6.75' do  
Set sq'd cedar post adjacent.  
E= 7885230.107 N= 176182.110

(13) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
7" Sugar N65°E 13.1' mrkd "1/16S BT"  
3" Sugar S41°E 9.6' do  
6" Sugar S79°W 4.5' do  
11" Sugar N03°E 10.2' do  
Set sq'd cedar post adjacent.  
E= 7888015.140 N= 175317.585

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.  
Coord. Ref.=NGS PID RL0476: N= 196482.411 m. E= 7879234.516 m.

Signed by Stephan J. Szyszkoski Date 08/06/2015  
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division

Register of Deeds Stamp & File Number													
1	A	B	C	D	E	F	G	H	I	J	K	L	M
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

