

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____ T _____ R _____ T _____ R _____	_____ _____ _____
2. Property Controlling in Section	S 32 T 46N R 34W S _____ T _____ R _____ S 32 T 46N R 34W	8 (GCDB 220140) 4
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	(GCDB 220160) _____
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 8 06/01/15 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(8-Sec. 32) Center-West 1/16 corner, Section 32. Found no record of prior monumentation.

(4-Sec. 32) Northwest 1/16 corner, Section 32. Not previously monumented.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(8-Sec. 32) Established the position for the corner midway and on a straight line between Quarter
corner 1322.00' west and the Center of Section 32 1322.00' east.

(4-Sec. 32) Established the position for the corner at the intersection of 1/16 lines. The
direction of the West 1/16 line is the weighted mean bearing of the N-S 1/4 line and the West
Section line. 1/16 corner #3 was established at 1318.50' north of C12 (1/2 of the distance C13-C12)
and on the extension of line C13-C12.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(8) Set 1"IDx32" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
11" Spruce S79°W 7.6' mrkd "1/16S BT"
9" Spruce N26°E 19.1' do
4" Spruce N75°E 17.35' do
6" Balsam S03°E 52.0' do
Fd. 1.25" ID iron pipe S10°E 29.81'
Set sq'd cedar post adjacent.
E= 7877542.092 N= 174300.429

(4) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
3" Balsam North 4.25' mrkd "1/16S BT"
6" Maple S64°E 7.65' do
11" W.Birch S18°E 7.0' do
6" Balsam S32°W 21.1' do
Set sq'd cedar post adjacent.
E= 7877552.237 N= 174702.465

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.
Coord. Ref.=NGS PID RL0476: N= 196482.411 m. E= 7879234.516 m.

Signed by Stephan J. Szyszkoski Date 07/08/2015
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division