

SURVEY & REMONUMENTATION

FEB 21 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filling Requirement of Act 74, Mich. P.A. 1970

For corners in

IRON

Located In:

Corner Code#

BATES TOWNSHIP

1. Public Land Survey

T 46 N, R 35 W C-10 S (SOUTH MEANDER)
(001)

2. Property controlling
in Section

3. Miscellaneous
Property in Sec.

S _____
S _____
S _____
S _____

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

SOUTH MEANDER CORNER BETWEEN SECTIONS 30 & 29

I, STEVEN R. APPELKAMP, in a field survey on NOVEMBER 9, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by decree of a Court of law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

ORIGINAL CORNER ESTABLISHED BY HARVEY MELLEN, U.S. DEPUTY SURVEYOR ON JUNE 12, 1851.

ORIGINAL BEARING TREES: SPRUCE 6" TAMARACK 10"
S 72°E S 79°W
4 LINKS 25 LINKS
2.64' 16.50'

1983 GARY PISONI P.S. 27457 SET A STANDARD 2" I.D. BY 30" LONG SPLIT BASE ALUMINUM MONUMENT BY SINGLE PROPORTIONATE MEASUREMENT ON LINE BETWEEN THE SOUTHEAST CORNER OF SECTION 30 AND THE NORTH MEANDER CORNER BETWEEN SECTIONS 30 AND 29. STAMPED AS FOLLOWS: M.C.; S-30, S-29, T46N, R35W, 1982, RLS 27457, RECORDED IN LIBER 5, PAGE 14. HE MADE THE FOLLOWING BEARING TREES.

W. BIRCH 10" BALSAM 6" B. SPRUCE 8"
S 27°30'W S 55°W S 89°W
39.97' 61.60' 61.59'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND MEANDER CORNER IN GOOD CONDITION AS RECORDED IN 1983 AS PER ACT 74, ACCEPTED CORNER POSITION AS IT MATCHED THE BEARING TREES FOUND.

EXISTING W. BIRCH 12" EXISTING STEEL SIGN POST
S 33°W S 88°W
40.02' 10.53'

PEER GROUP APPROVED

Harvey Mellen 11-30-2000
COUNTY REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

THE MEANDER CORNER IS FLUSH WITH THE GROUND 15' SOUTH OF WATER 3" CAST ALUMINUM CAP STAMPED AND IN THE ORIGINAL POSITION PER THE 1983 ACT 74 LAND CORNER RECORDATION CERTIFICATE. WE MADE THE FOLLOWING REFERENCES.

BALSAM 14" W. BIRCH 7" SPRUCE 9"
S 57°E S 14°E N 88°W
9.02' 51.40' 61.56'



Signed by

Steven R. Appenkamp

Date

NOVEMBER 9, 2000

Surveyor's Michigan License No. 43045