## SURVEY & REMONUMENTATION

FEB 21 2001

SECTION

SECTION					
For corners in		ORNER RECORDATI Requirement of Act 74		COMMENCING RECEIVELT IRON COUNTY	R RECORD
<u>IRON</u>	Located In:	Corner Code#		00 DEC -4	AM ID. CO
BATES TOWNSHIP				9 Rosell	AT 10: US 1
1. Public Land Survey	T 46 N, R 35	W C-10 N (NORTH N	IEANDER)	. Recays:	X, 0) 1, 18 62
				Coilied	L. 8, P. 182
<ul><li>2. Property controlling in Section</li><li>3. Miscellaneous Property in Sec.</li></ul>	ssss			के जिल्हा है। egister of Deeds Sta	TO THE STATES
, , , , , , , , , , , , , , , , , , , ,				egister of Deeds of	Imp a the Hamber
4. Lot No, Record	ed Plat		1 A B	CDEFGI	H 1 J K L M
NORTH MEANDER C	ORNER BETWEE	N SECTIONS 30 A	ND 29 3		
I, STEVEN R. APPLEKAMP requirements of P.A. 74, Michigan F conformance with regulations and n of the United States Department of and/or that the corner points mentio Michigan Board of Land Surveyors monumented, recovered, found as	P.A. of 1970, the corner poin ules therefore as required in the interior, Bureau of land M aned in lines 3,4 and 5 above or by Decree of a Court of La	ts mentioned in lines 1 and 2 the current manual of survey i Management of by decree of a were in conformance with the	state that under 4 bove were in structions 5 Court of law rules of the	17 16 20 21 21	15 14 13
NOTE: Not more than 2 corne on this certificate.	ers, all in the same town	and range, may be record	ed 9	29 28	27 26 25
A. Description of original mon-	ument and accessories	and/or subsequent restorate	ion: 11	32 33	34 35 36
ORIGINAL CORNER ESTAB		·	12   31		
JUNE 12, 1851.	CIONED DI TIANGET MEE	ELN, 0.0. DE. 0 11 0011101	-1.5	•	
ORIGINAL BEARING TREES	6" N 50°W N	RUCE 5" 78°E LINKS			
1968 DONALD D. LAPPALA F M.C.; R.L.S. 12585; 1968 RECORDED IN LIBER 3	P.S. 12535 SET A 2" I.D. B B, AFTER RECOVERING T	Y 5 FEET LONG GALVANIZ WO ORIGINAL BEARING TI	REES HE MADE THE FOI	LOWING BEARING	IKEES.
	V. PINE W. PINE	B-SPRUCE B-SPRU 5" 4"	CE ADDED TWO E	PISONI AND MARK S BEARING TREES BEG	CAUSE
	7" 10"   10°W \$ 68°E   42.4" 11.0"	N 80°E N 36°30 21,70' 17.54'	W THE W-PINE P	ROM 1968 IS NOW D	EAD.
B. Description of corner evider	nce found and/or method	d applied in restoring or rea ON AS RECORDED IN 1968 MATCHED THE BEARING	AS PER LAND CORNER		
				PEER GROUP A	PPROVED
			De		11-30-2000
		•		COUNTY REPRE	SENTATIVE
C. Description of monument t	for corner and accessorie	es established to perpetua	te locating the position o	f the corner:	pocae.
THE MEANDER CORNER	R IS 2 FEET ABOVE GROU DRIGINAL POSITION PER	JND A 3" BRONZE TABLE" THE 1968 LAND CORNER	ON A 2" GALV. PIPE	CATE.	STEVEN *
	EXISTING W. PINE B-SRUCE 13" 7"	EXISTING EXISTING B. SPRUCE 5" 5"	SET STEEL SIGN PO NEXT TO MONUMEN TO STABLILIZE COR	ST FO PA	OFESSIONAL CU SURVEYOR NO.
N 83°E 21.90'	S 68°E N 75°W 11.00' 8.66'	N 72°W N 33°W 18.23' 17.75'			
λ,	$\mathcal{O}$				FESSION
Signed by	K. / Apply	1	DateNOVI	EMBER 9, 2000	
Surveyor's Michigan License	No4304	5			