LAND CORNER RECORDATION CERTIFICATE

JAN 192001

Filing Requirement of Act 74, Mich. P.A. 1970 Isabella County Remonumentation

RECTION

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN.28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983

For Corners in Isabella			200000011033 Filed for Record in ISABELLA COUNTY, MI
(County)	Located In:	Corner Code#:	SHARON A BROWN On 12-19-2000 At 09:07:52 am. RE LAND COR 9.00
4. Lot No	T13N R3W T R T R S T R S T R. T R. T R. T R. T R.		Liber 2 Page 5 - 5 OS Register of Deeds Stamp & File Number
I, Jan S. Fokens, in a field survey 74, Michigan P.A. of 1970, the cwith regulations and rules theref United States Department of the Law and/or that the corner point rules of the Michigan Board of I established, monumented, re-months of the Michigan Board of I established, monumented, re-months of the Michigan Board of I established, monumented, re-months of the Michigan Board of I established, monumented, re-months of the Michigan Board of I established in the Michigan Board of I	y on March 2, 2000, do hereby certify corner points mentioned in lines 1 and fore as required in the current manual of Interior, Bureau of Land Management is mentioned in lines 3, 4 and 5 above v. and Surveyors or by a Decree of a Commented, recovered, found as expressions.	that under requirements of P.A 2 above were in conformance of survey instructions of the or by a decree of a Court of were in conformance with the urt of Law, established, resed below.	2-6-5-4-3-2-1- 3-4-7-8-9-10-11-12- 5-4-17-16-15-14-13- 7-4-13-17-16-15-14-13-
recorded on this certific			8-19-20-21-22-23-24- 9-1-10-30-29-28-27-26-25- 11-12-31-32-33-34-35-36-
restoration:	nal monument and accessori	es and/or subsequent	ACCEPTED BY THE ISABELLA CO BEMONUMENTATION PEUR CRO
Subdivision: H	v: obert Clark Jr. 2 nd Quarter (iriam Burnham 3 nd Quarter , & 71 original field notes	1831 1832	ON 6, 28, 69 William B. Ruddell, PS County Representative
 County Survey Records: Liber 1, Page 132 A.K. Herrington June 1880 Found stone set by P. Ester when he grated the road L.C.R.C.: Liber 1, Page 201 William Ruddell Recorded date June 10, 1974 Found 1" solid rod in monument box Liber 4, page 1265 Gerry Gray Recorded date July 20, 1994 Found 1" rod in monument box Surveys of Record: Liber 001, Page 693 Ruddell Engineering January, 1975 Found iron in monument box Isabella County Road Commission: No information available Unrecorded Surveys:			
B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:			
This corner established in Isabella County Remonumentation Program. See dossier for detailed report. This is an existent corner. 1. Found 2.0' long spike pointed on the end with a 1" head in monument box 2. At excavation depth of 1.7' a large stone was found. 3. Bottom of spike was found 0.15' West of top of stone and tipped over stone to perpetuate it. 2. Excavated to 2.0'. Found no further evidence			
 C. Description of monum 	lable evidence of the position of the for corner and accessories bella County Monument in Mo	established to perpetuate	r and replaced with Standard Monument Corner. e locating the position of the corner: 3-5 and PS 21567.
B-5 N. 1/4 N.31°W. S.43°W. N.64°E. S.19°E. N.89°39'28"W. S.89°49'49"E.	85.15' Found nail and tag 62.35' Found nail and tag 42.80' Set LSC nail and 2541.99' (A-5) NW. Corne 2655.84' (C-5) NE. Corner	g in E. face of 12" Elm to g in NW. face of power p g in 14" Ash tree tag in E. face of Blue Sp tr, Section 18, T.13N-R.3 , Section 18, T.13N-R.3	ree (Liber 4, page 1265, L.C.R.C.) pole