Signed by_

Surveyor's Michigan License No. 21567

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 Isabella County Remonumentation

JAN 1 9 2001

FCTION

For Corners in <u>Isabella</u>			200000011040 Filed for Record in ISABELLA COUNTY, MI
(County)	Located In:	Corner Code#:	SHARON A BROWN On 12-19-2000 At 09:09:22 am. RE LAND COR 9.00
1. Public Land Survey	T. <u>16N</u> R. <u>6W</u> T. <u>R.</u> T. <u>R.</u>	A-1	Liber 2 Page 12 - 12
2. Public Controlling in Section3. Miscellaneous	S T R S T R S T R.		
Property in Section 4. Lot No. 5. Private Claims	S T R, Recorded Plat		Register of Deeds Stamp & File Number
I, Jan S. Fokens, in a field surve, 74, Michigan P.A. of 1970, the c with regulations and rules theref United States Department of the Law and/or that the corner point rules of the Michigan Board of I	y on May 12, 2000, do hereby certify the corner points mentioned in lines 1 and 2 ore as required in the current manual of Interior, Bureau of Land Management is mentioned in lines 3, 4 and 5 above wand Surveyors or by a Decree of a Connumented, recovered, found as express	2 above were in conformance f survey instructions of the or by a decree of a Court of were in conformance with the art of I aw, established, re-	1ABCDEFGHIJKLM 2 6 5 4 3 2 1 3 4 7 8 9 10 11 12 5 5 6 18 17 16 15 14 13 6 7
NOTE: Not more than 2 recorded on this certification.	corners, all in the same town ate.	and range, may be	8-19-20-21-22-23-24 9-19-10-30-29-28-27-26-25
	al monument and accessorie	es and/or subsequent	11
Pages 299, 308, 3 2. County Survey Record	Quarter, 1837 John Hodgson 714 original field notes s:		veyor 1895, found one OB tree, considered corner good
Liber 4, Page 55	(Clare Co.) Arthur Johnson Hemlock 24 S1E	Distances noted October 1905	had a da
Liber 6, Page 176	A-13 to B-13 38. 5 (Clare Co.) Hemlock 24 S1E	41 ch (2535.06') 3 18	Market to the second
Liber 404, Page 8 4. Surveys of Record: None of record 5. Unrecorded Survey:	2 Alva Courtright 1972 For 31 Paul B. Lapham 1981 For & Associates 1993 Found plo	und plow point	ection of roads
B. Description of corner e This existent con 1. Found axle sh Top was dama 2. Said axle shaf	vidence found and/or method a ner established in Clare County	pplied in restoring or re- Remonumentation Prog ection corner found by p and. 5" guard stones	restablishing corner: gram. See dossier for detailed report. previous surveyors was the 1 3/4" end without the gearing
C. Description of monume Set Standard Clar and PS 21567.	ent for corner and accessories es e County Monument in Monum	stablished to perpetuate nent Box, stamped A-13	replaced with Standard Monument Corner. locating the position of the corner: //17-6 and A-1/16-6 and M-13/17-7 and M-1/16-7
N.42°W. N.25°E. South S.62°W.	91.55' Set nail and tag in We 32.39' Found nail and disc #	uth face of 4" White Pinest face of 12" Maple (pr 9433 in E. face of wood rth face of 15" Maple C	e revious witness of 20" Maple is dead)