JACKSON COUNTY LIBER 1451 PAGE 182 APPROVED LAND CORNER GENTER OF SECTION 25, SPRING ARBOR TWP. P.A. 345 of 1990/ Chairman A LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 For corners in STATE OF MICHIGAN Jackson JACKSON COUNTY Located In: Corner Code ## (County) RECORDED T 3S R 2W 1. Public Land Survey 30 DEC 94 11:21 A.M. — REMONUMENTATION GERALD J. McDEVITT \_ R \_\_ RESISTER OF DEEDS 2. Property Controlling \_ T \_\_\_\_ R \_\_ MAY 0 3 **199**5 in Section S \_\_\_ T \_\_\_\_ R \_ \_\_\_ T \_\_\_\_ R \_ Miscellaneous S Register of Deeds Stamp & File Number COMMISSION Property in Sec. \_\_ , Recorded Plat \_\_ 4. Lot No. \_\_ 5. Private Claims \_\_ Pierson PS in a field survey on December 2 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below: NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate. A. Description of original monument and accessories and/or subsequent restoration: L-10 - This position not established by original government surveyors. \$ 2.00 REMONUMENTATION \$ 7.00 CORNER REMONUMENTATION B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: Section 25, Spring Arbor Township L-10 - Intersected lines from opposite quarter section corners. Found 1" Hex-head bolt -N12°E- 2.85' from monument set. Set Standard Jackson County Monument (Physical centerline of road -South- 63,90') ARDEN S **PIERSON** C. Description of monument for corner and accessories established to perpetuate locating the post of the toose

L-10 (Center of Section 25)

Jackson County Monument

Center metal flag pole -N14°E- 73.81 Nail & tag #13039 W. side 12" Pine -N38°E- 96.48' Nail & tag #13039 W. side 16" Oak -S32°W- 112.52' Nail & tag #13039 S. side 16" Oak -S68°E- 107.30'

\*Standard Jackson County Monument is a 1/2" iron rod 36" long with a Jackson County Remonumentation disk encased in a 4" concrete cylinder.

Signed by Olde S. Frem		Date	December 6, 1994	
Surveyor's Michigan License No.	13039			
Stirvevor's Michigan License no.	T 0 0 0 2			