

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

KALKASKA
(County)

Located in:

Corner Code #

2000 REMONUMENTATION

1. Public Land Survey

T 25N R 5W

L-9

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

**SURVEY &
REMONUMENTATION**

FEB 26 2001

SECTION

I, EUGENE FARRIER, in a field survey on August 9, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		6		5		4		3		2		1
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

L-9; 1/4 Cor. Common to Secs. 24 & 25, T25N-R5W, Garfield Township

July 28, 1852 GLO Resurvey by George H. Cannon, set Pine post for corner; Sp. Pine 10" N 31° E 90 links.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

L-9; 1/4 Cor. Common to Secs. 24 & 25, T25N-R5W, Garfield Township

Set 5/8" iron with brass cap in mon box, single proportion between found section corners 1.0' N of centerline road. N 52° W, 63.25' set nail and washer in 8" J. Pine; N 02° E, 36.82' set nail and washer in 8" J. Pine; N 60° E, 60.27' set nail and washer in 6" J. Pine; S 25° W, 79.17' set nail and washer in 7" R. Pine.

No G.L.O. witnesses were found.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-9; 1/4 Cor. Common to Secs. 24 & 25, T25N-R5W, Garfield Township

Set 5/8" iron with brass cap in mon box, single proportion between found section corners 1.0' N of centerline road.

N 52° W, 63.25' set nail and washer in 8" J. Pine

N 02° E, 36.82' set nail and washer in 8" J. Pine

N 60° E, 60.27' set nail and washer in 6" J. Pine

S 25° W, 79.17' set nail and washer in 7" R. Pine.

Kalkaska County Peer Group accepted the above monument as a careful and faithful reestablishment of the position of the original corner.

Ratified by Peer Group


P.A. 345 - 1990 Kalkaska County

Chairman Eugene Farrier

Date 2-14-01

Signed by Eugene Farrier
Surveyor's Michigan License No. 24594

Date 2-15-01



3026816
Page: 1 of 1
02/15/2001 10:26A
REMON
LB: 6 PG: 145

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1976
REVISED JAN., 1983
REVISED OCT., 1986

Kalkaska County Joan Hall, Register