

SURVEY &
REMONUMENTATION

FEB 13 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

KALKASKA Located In: Corner Code #
(County)
1997 REMONUMENTATION
1. Public Land Survey T 26N R 7W B-3
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, EUGENE FARRIER, in a field survey on OCTOBER 10, 1997
do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as
required in the current manual of survey instructions of the United States Department of the Interior,
Bureau of Land Management or by a decree of a Court of Law and /or that the corner points
mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of
Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented,
recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:
B-3: Cor. common Sec. 6 & 7, T26N-R7W, Orange Township
1849, GLO resurvey, set Hemlock Post. 10" Cedar S40E, 11, 11" Cedar N51W, 7
08-20-1987, C. Roser #12028 LCR drove 5/8" x 34" rerod w/cap, w/accessories, Lib. 2, Pg. 351
09-04-1991, Farrier Surveying, survey, fd. DNR brass cap, w/accessories
05-20-1992, Farrier Surveying, survey, fd. DNR brass cap, w/accessories
05-01-1994, Farrier Surveying, survey, fd. DNR brass cap, w/accessories

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
B-3: Cor. common Sec. 6 & 7, T26N-R7W, Orange Township
Fd. 5/8" iron & cap DNR, removed cap, placed S.C.M. (Brass) on iron in C.L. Gregg Rd. No GLO witnesses were fd. The Kalkaska Co.
Peer group approved & accepted the above monument as a careful and faithful reestablishment of the position of the original corner.



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
B-3: Cor. common Sec. 6 & 7, T26N-R7W, Orange Township
Fd. 5/8" iron & cap DNR, removed cap, placed S.C.M. (Brass) on iron in C.L. Gregg Rd.
Fd. N6E DNR Cedar Post, 33.00'
Fd. Nail N40E 5" W. Pine, 57.65'
Fd. Nail S48E 14" Maple, 52.60'
Fd. Nail S49W 8" Cedar, 58.65'
Fd. Nail N34W 8" Tw. Maple, 33.77'

Ratified by Peer Group
P.A. 345 - 1990 Kalkaska County
Chairman Eugene Farrier
Date 1-29-98

Signed by Eugene Farrier Date 2-3-98 Surveyor's
Michigan License No. 24594