

SURVEY &
REMONUMENTATION

FEB 13 1998

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For corners in

KALKASKA
(County)

Located In:

Corner Code #

1997 REMONUMENTATION

1. Public Land Survey

T.26N R.7W

C-10

T. R.

T. R.

T. R.

2. Property Controlling
in Section

S. T. R.

S. T. R.

3. Miscellaneous
Property in Sec.

S. T. R.

S. T. R.

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, EUGENE FARRIER, in a field survey on OCTOBER 28, 1997

do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

| | A | B | C | D | E | F | G | H | I | J | K | L | M |
|----|---|----|---|----|---|----|---|----|---|----|---|----|---|
| 1 | | | | | | | | | | | | | |
| 2 | | 6 | | 5 | | 4 | | 3 | | 2 | | 1 | |
| 3 | | | | | | | | | | | | | |
| 4 | | 7 | | 8 | | 9 | | 10 | | 11 | | 12 | |
| 5 | | | | | | | | | | | | | |
| 6 | | 18 | | 17 | | 16 | | 15 | | 14 | | 13 | |
| 7 | | | | | | | | | | | | | |
| 8 | | 19 | | 20 | | 21 | | 22 | | 23 | | 24 | |
| 9 | | | | | | | | | | | | | |
| 10 | | 30 | | 29 | | 28 | | 27 | | 26 | | 25 | |
| 11 | | | | | | | | | | | | | |
| 12 | | 31 | | 32 | | 33 | | 34 | | 35 | | 36 | |
| 13 | | | | | | | | | | | | | |

A. Description of original monument and accessories and/or subsequent restoration:

C-10: Cor. common Sec. 29 & 30, T26N-R7W, Orange Township

1849, GLO resurvey, set Sugar post, 8" Hemlock N45W, 29, 15" Sugar S69E, 10

04-02-1910, County Surveyor, established cor. & set iron pipe, no accessories

04-04-1987, Farrier Surveying, Cert. Survey, fd. 1/2" rerod, w/accessories

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-10: Cor. common Sec. 29 & 30, T26N-R7W, Orange Township

Fd. 1/2" rebar 1' West of C.L. Ryckman Rd. on fence line to East. Pulled and replaced with 5/8" x 18" rebar, w/brass cap in mon. box. No GLO witnesses were fd. The Kalkaska Co. Peer group approved the above monument as careful and faithful reproduction of the position of the original corner.



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-10: Cor. common Sec. 29 & 30, T26N-R7W, Orange Township

Fd. 1/2" rebar 1' West of C.L. Ryckman Rd. on fence line to East. Pulled and replaced with 5/8" x 18" rebar, w/brass cap in mon. box. East iron & cap #23514, 32.24'

Set nail & tag S43W, 30" Maple, 43.50'

Set nail & tag S55W, 14" Maple, 42.53'

set nail & tag N36W, P. Pole, 50.00'

Ratified by Peer Group

P.A. 345 - 1990 Kalkaska County

Chairman Eugene Farrier

Date 1-29-98

Signed by Eugene Farrier

Surveyor's Michigan License No. 24594

Date 2-3-98



Kalkaska County

REMON

9.00

3004829

Page: 1 of 1

02/04/98 11:22A

LB: 5 PG: 233

FORM APPROVED BY MICHIGAN STATEBOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983
REVISED OCT., 1996