

JAN 17 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

KALKASKA

(County)

Located In:

Corner Code #1

1995 REMONUMENTATION

1. Public Land Survey T 26N R 7W L-1  
T R  
T R  
T R
2. Property Controlling S T R  
in Section S T R
3. Miscellaneous S T R  
Property in Sec. S T R

4. Lot No. , Recorded Plat
5. Private Claims

KALKASKA COUNTY, MICHIGAN  
RECEIVED  
95 DEC 27 AM 9:55

*Joan Hall*  
REG. DE. REC.

Register of Deeds Stamp & File Number

I, EUGENE FARRIER, in a field survey on Dec. 5, 19 95, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules theretore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

L-1: N 1/4 Corner, Sec. 1, T26N-R7W, Orange

This corner not established by original government surveyors: Nothing on record.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

L-1: N 1/4 Corner, Sec. 1, T26N-R7W, Orange

Set 5/8" x 18" R.B. w/aluminum cap. Set midway on online between NW & NE corners of Sec. 1, T26N-R7W. This position not established by original government surveyors. The Kalkaska Co. peer group approved the above monument and is accepted as the best available evidence of the position of the corner.

Ratified by Peer Group  
P.A. 345 - 1990 Kalkaska County  
Chairman *Eugene Farrier*  
Date 12-19-95

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-1: N 1/4 Corner, Sec. 1, T26N-R7W, Orange

Set 5/8" x 18" R.B. w/aluminum cap.

Set nail & tag N60E, 8" Cedar, 10.53'

East, S 1/4 Cor., Sec. 36, T27N-R7W, Kal.Co.Mon, 13.86'

Set nail & tag N20W, 7" Spruce, 22.63'

Set nail & tag N11E, 13" Cedar, 23.83'

Signed by *Eugene Farrier*  
Surveyor's Michigan License No. 24594

Date 12-22-95

