LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970			
For corners in	rning Keda	irement of Act /4, Mich. F	.A. 1970
KALKASKA	Located in:	Corner Code #	SURVEY &
2000 REMONUMENTATION 1. Public Land Survey	T <u>27N</u> R <u>8W</u> T <u>26N</u> R <u>8W</u> T R	A-13 A-1	REMONUMENTATION FEB 26 2001
Property Controlling in Section Miscellaneous Property in Sec.	TR S T R S T R S T R S T R		SECTION
4, Lot No, Recorded Plat			
5. Private Claims			A B C D E F G K I J K L M
			2 - 6 - 5 - 4 - 3 - 2 - 1 - 3 3 - 4 - 7 - 8 - 9 - 10 - 11 - 12 -
I, <u>FUGENE FARRIER</u> , in a field survey on <u>NOVEMBER</u> , 20 00 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Dacree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:			nes 1 6 19 17 16 15 14 13 14 13 15 14 13 15 15 14 13 15 15 15 15 15 15 15 15 15 15 15 15 15
NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.			11 32 31 32 33 34 35 36
A-13: Section Corner Common to Secs. 31. T27N-R8W: & A-1: Sec. 6, T26N-R8W Wood post witnessed by a 22* Pine N 29*W, 33 links; and 20* Pine S57°E, 5 links, U.S. survey by Alvin Burt (Deputy Surveyor), deted April 12, 1839. Original Corner, survey index by M. Schaef (DNR Surveyor), deted around 1930. Found from in centerline of trells North, South, East, and West, Land Corner Record by Jerry L. Wilcox, deted 1-15-73, and recorded in Liber 1 Page 171 of the Land Corner Records of Kalkaska County. Found Corner recorded in Liber 1 Page 171 of the Land Corner Records Kalkaska County and replaced with a 2 1/2" x 30* flanged bottom galvanized iron pipe with 3 1/4* brass cap stamped GRAND TRAVERSE COUNTY REMONUMENTATION, 12* below the surface of the ground, a Land Corner Record by Michael Mileski, dated 9-10-1993 and recorded in Liber 3 Page 25 of the Kalkaska County Land Corner Records.			
B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: A-13: Section Corner Common to Secs. 31. T27N-R8W: & A-1: Sec. 6. T26N-R8W Found 3" iron pipe in a four-way trail road intersection as recorded in Liber 3 Page 25 of the Land Corner Records of Kalkeska County, and is accepted as a careful and faithful perpetuation of the position of the original corner and a 2 1/2" x 30" flanged bottom galvanized iron pipe with 3 1/4" brass cap stamped GRAND TRAVERSE COUNTY REMONUMENTATION, was placed as disclosed in the Land Corner recorded in Liber 3 Page 25 of the Kalkeska County Land Corner Records.			
LCRC by Robert F. Mitchell December 28, 1993 and recorded in Liber 3 Page 480 Grand Traverse County; N23° E, 12" White Oak, 53.18'; S 45°E, 4" Red Pine, 43.12'; S 37°W, 10" Red Pine, 63.58', N 60°W, 7" Red Pine, 40.71'.			
Corner approved the Grand Traverse County Peer Review Group on 12-15-93.			
A-13: Section Corner Common Found standard Grand Traverse C N23°E - 12" White Pine -53.18 S45°E - 4" Red Pine - 43.12' S37°W - 10" Red Pine - 63.58' N80°W - 7" Red Pine - 40.71'	county Monument referenced in	& A-1: Sec. 6, T26N-R6W Liber 3 Page 480 Grand Traver	
i ² .A. 345 - 1990 Kalka			* EUGENE D. *
Chairman	4-01		FARRIER * PROFESSIONAL SURVEYOR
Signed by Surveyor's Michigan License No.	24594		Date 2-15-4 1 24594
Kalkaska County Joan Hal	3026: Page: 1 02/18/200 1, Register LB: 6 PG	915 of 1 101 10:26A	ED BY MICHIGIAN STATE BOAND OF PROFESSION AND PROFE