LAND CORNER RECORDATION CERTIFICATE Filling Requirement of Act 74 Mich. P.A. 1970

_	Filing Requir	ement of Act 74, Mich. P.A. 19	70 01170/20/ 9
For corners in			" SURVEY & REMONUMENTATION
KALKASKA (County)	Located In:	Corner Code #	
2000 REMONUMENTATION 1. Public Land Survey	<u>T 27N R 6W</u>	G-5	FEB 26 2001
	TR TR TR		SECTION
Property Controlling in Section Miscellaneous	S TR S TR S TR	-	
Property in Sec.	S T R		
4. Lot No, Recor	ded Plat		
5. Private Claims			A B C D E F G H I J K L M
			2 6 5 4 3 2 1
			3
I, EUGENE FARRIER , in a	field survey on <u>August 21</u> ,	20_00_ do hereby state that under	5 9 10 11 12
requirements of P.A. 74. Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey			6 18 17 16 15 14 13
decree of a Court of Law and /or	that the corner points mentioned	reau of Land Management or by a d in lines 3, 4 and 5 above were in	7
conformance with the rules of the Law; established, re-established,	ne Michigan Board of Land Surve monumented, recovered, found a	yors or by a Decree of a Court of a expressed below:	8 19 20 21 22 23 24
NOTE: Not more than 2 corners, all in the same town and range, may be recorded		10 30 29 28 27 26 25	
on this certificate.		·	11
A Department of external and			12 31 32 33 34 35 36
A. Description of original mo G-5; Sec. Cor. Common to Se 1852: GLO resurvey by G. H. Car 107, S 40°E, 25 links.	cs. 9. 10. 15 & 16. T27N-R6 nnan; set post for corner; Hemioc	W. Excelsior Township ok 24°, N 85°W, 21 links; Sugar	
1902: Survey by W.S. Merrill, Co 1902: Survey drawing by W. S. M 1974: LCRC by L.M. Gershbachel 53.85'; R.R. spike in Guy pole, N 1980: Surveys by J.L. Fletcher in cap#18890, S 38°W, 53.83'; fot 35.77'. 1990: Survey by B.M. Jones in Li	nty Surveyor; visited corner; no a nty Surveyor in Book 5 Page 24; unty Surveyor in Book 12 Page 6 ferrill, County Surveyor. Into trecorded); found 3/4" x 7" 45°W, 45.77' (heeds); USGS-TI Liber 2 Pages 675-697; found o und neil in 9" R. Pine, S 40°E, 6; ber 3 Pages 337-338; found spilk corded); found boat spike in cen	ccessories. visited corner; Sugar 18", 5 66°W, 'i6; found corner stake and one bearir disc. End, raised with cabin spike; 7' BM elevation = 1208,11'; 5" R. Pine, abin spike; found R.R. spike in Guy P 3.74'; found nail in 7" R. Pine, N 45° 18. cap #19830. no accessories.	19 links; Beach 11", N 03.13°E, 3.6 links, no tree, Hemlock N-W by assistance of Ed Harding. "R. Pine, S 50°E, 63.70'; Power pole, S 38°W, N 42°E, 66.35'. ole, S 45°W, 45.80'; found neil in Power pole E, 66.38'; found large epike in 8" R. Pine, N 65°E, N 38°E, 26.75'; 8" Maple, N 53°W, 57.00';
B. Description of corner evidence G-5: Sec. Cor. Common to Ser Found 5/8" iron rod in mon box, of R. Pine, S 40°E, 63.81°; found sp No G.L.O. witnesses were found.	os. 9. 10. 15 & 16. T27N-R6	W. Excelsior Township 'east centerline Darks Road: found a	pike 10" R. Pine, N 45°E, 86.26'; found spike 8" 72.74'. Added standard county monument.
G-5: Sec. Cor. Common to Sec	cs. 9. 10. 15 & 16. T27N-R6	ed to perpetuate locating the position W. Excelsior Township east centerline Darke Road; added a	
N 45°E, 66.26', 10" R. Pine, four S 40°E, 63.81', 8" R. Pine, found S 44°W, 53.80'power pole, found	l spike		MARKE OF MICHAEL
N 55°W, 72.74', 8" Red Pine, for	·		* EUGENE D. *
Raikaska County Peer Group acce	pted the above monument as the	best available evidence of the position	on of the original corner FARRIER PROFESSIONAL
Signal by Company	FINA	_ •	No. 24594
Surveyor's Michigan License No.	24594	Date	The state of the s
		FORM APPROVED BY MIC	HIGAN STATE ROARD OF PROFESSIONAL SURVEY BOOK 14,1971 REVISED MAY 14,1975
Ratified by Peer Group P.A. 345 - 1990 Kalkas	ska County		REVISED JAN., 1983 REVISED OCT., 1998
Chairman	James .		**************************************
Date	4-01		Page: 1 of 1